

Blue Lake City Council Agenda Tuesday, November 19, 2013 Regular Meeting @ 7:00 p.m. to 9:30 p.m. Community Center – 111 Greenwood (Skinner Store Building behind City Hall)

Unless Otherwise Noted, All Items on the Agenda Are Subject to Council Action.

- 1. Flag Salute/Establish a Quorum of the Council
- 2. <u>Motion to Approve Agenda</u>
- 3. Public Input The Public is invited to present petitions, make announcements, or provide other information to the City Council that is relevant to the scope of authority of the City of Blue Lake that is not on the Agenda. The Council may provide up to 15 minutes for this public input session. To assure that each individual presentation is heard, the Council may uniformly impose time limitations of 3 minutes to each individual presentation. The public will be given the opportunity to address items that are on the agenda at the time the Council takes up each specific agenda item
- 4. <u>Sewer Capacity Analysis with Mitigation Mad River Brewery (Presentation by City Engineer)</u>
- 5. <u>Council Approval to Submit CDBG Program Income-Funded Waiver (Action)</u>
- 6. Michael Fields, Dell Arte: Art Place Activities and Thoughts (Presentation)
- 7. <u>Award by CWEA to City of Blue Lake, "Waste Water Plant of the Year"</u> (Announcement)
- 8. <u>Sherman Schapiro, Blue Lake Resident, 110 Greenwood SHN Greenwood Road Geometric Assessment Report of Findings Re-Visited with Recommended Changes</u>
- 9. Councilmember Manzanita: Legislative Matters (a.) Proposed Humboldt Waste Management Authority Goals (Action) (b.) Report from California League of Cities Webinar (Discussion) (c) Expand Business in Business Park (Discussion)
- 10. Grant Opportunity Resurfacing of Railroad Avenue Between E and G Streets
- 11. Consent Agenda
 - a. October 2013 Disbursements/Warrants
- 12. Reports of Council and Staff
- 13. Motion to Adopt Minutes from
 - a. November 5, 2013
 - b. November 7, 2013

14. Future Agenda Items

15. Correspondence

Note: A Motion to Enter Into Closed Session to Discuss the Following Subjects Appropriately

Closed Session: Pursuant to Government Code Section 54956.8 – Conference with Negotiator Regarding Renewal of Blue Lake Power Lease, 200 Taylor Way Agency Negotiator: City Manager John Berchtold Negotiating Parties: City of Blue Lake and Blue Lake Power, LLC Under Negotiation: Lease Term

Note: Upon Conclusion of the Closed Session, the Council Shall Report Any Action Taken in Closed Session (Government Code 54957.1)

16. Motion to Adjourn

A request for disability-related modification or accommodation, including auxiliary aid or services, may be made by a person with a disability who requires a modification or accommodation in order to participate in the public meeting, by contacting City Manager John Berchtold at least 24 hours prior to the commencement of the meeting.

To: Mayor and Councilmembers From: John Berchtold, City Manager

Date: November 13, 2013

Subject: Aeration Analysis – Blue Lake WWTF – Impact of Brewery Effluent

Please find enclosed the technical report prepared by SHN relative to the Brewery's request for additional sewer capacity. City Engineer Foget will provide an Executive Summary of this report.

Please pay particular attention to the recommendations found on pages 5 and 6. Two (2) additional aerators, installed after placement of the baffle curtain, will provide the additional capacity requested by the Brewery. In fact, oxygen generation exceeds oxygen generation by 27%. This then becomes the basis of a cost share by the City for 27% of \$77,000.00 or \$20,790.00. Funding could come from Fund 72, Capital Improvement/Replacement. It only makes sense to go with two (2) additional aerators of 5hp each instead of one 7.5 hp aerator. This is a unique opportunity to maximize capacity.

Staff and the Brewery are working thru the Report and I am pleased to share that there is fundamental agreement.

The purpose of the Engineer's Report is to keep City Council up to date. It is not a negotiating session between the Brewery and City Council. No action is required at this time; however, your comments are welcome on the upsizing of aerators necessary. Due to the technical nature of this Report, I would be pleased to meet with any Councilperson on a one to one basis.



CONSULTING ENGINEERS & GEOLOGISTS, INC.

275 Market Avenue • Coos Bay, Oregon 97420-2228 • Phone: 541/266-9890 • FAX: 541/266-9496 • shninfo@shn-engr.com

Technical Memorandum

Reference:	013003.701
Date:	November 7, 2013
To:	John Berchtold, City Manager
Copy to:	Neil Carnam, Mad River Brewery
From:	Steve Donovan, Mike Foget, Susan Foreman
Subject:	Aeration Analysis Blue Lake WWTF, Impact of Brewery Effluent

The Blue Lake Wastewater Treatment Facility (BLWWTF) is a facultative lagoon system with supplemental aeration in the first cell. The results of a local limits analysis recently completed for the facility by SHN indicate the treatment system is near capacity. The Mad River Brewery (MRB), a current industrial client, has applied to the City for an increase in its permitted discharge. SHN has been asked to prepare an analysis of the impact from an increase in MRB's discharge of biological oxygen demand (BOD) on the level of treatment provided. It is anticipated that increasing aeration capacity would increase treatment capacity sufficiently to allow the increased load from the MRB. This memorandum addressed the aeration requirement, required upgrades, and cost share with MRB.


Analysis

Current biological oxygen demand (BOD) loadings were obtained from the City's Annual Selfmonitoring Reports for 2011 and 2012 (see Attachment 1). From these reports, it was determined that the Average Dry Weather Flow (May through October) and average BOD are 0.14 million gallons per day (MGD) and 231 milligrams per liter (mg/l), respectively. Based on this influent flow and BOD concentration the average daily BOD loading on the facility is estimated at 270 pounds per day (ppd). The loading includes existing contributions from the brewery.

The brewery has requested a 90 ppd increase in BOD loading, resulting in a proportional increase in dissolved oxygen (DO) demand on the lagoon system. The analysis assumes that the increased loading will be discharged during a minimum 12-hour period and that the discharge will be pH neutral. MRB has indicated that the increased brewery waste load would not contribute significantly to the ammonia nitrogen loading which has been assumed to average 35 mg/l for all wastewater contributions.

Aeration requirements were evaluated for each basin in the facility. The analysis assumes that Pond A is divided into two sections, 1A and 1B, by a floating baffle curtain that is scheduled to be installed within the next 12 months (Figure 1).

Civil • Environmental • Geotechnical • Surveying Construction Monitoring • Materials Testing Economic Development • Planning & Permitting



Mr. John Berchtold, City Manager **Aeration Analysis Blue Lake WWTF, Impact of Brewery Effluent** November 7, 2013 Page 2 of 5

Dissolved Oxygen Demand

An analysis of the increase in oxygen demand requires calculation of the Actual Oxygen Required (AOR) and the equivalent oxygen transfer rate at standard conditions (the Standard Oxygen Requirement or SOR).

To estimate AOR, the following assumptions were made:

- 2.5 lbs O₂/lb. BOD removed
- 4.6 lbs O₂/lb NH₃-N removed

The SOR is the amount of oxygen that must be supplied in order to provide the oxygen required. Oxygen transfer is driven by the difference between DO saturation concentration and the actual concentration of DO in the wastewater. The SOR depends upon the oxygen transfer efficiency. SOR is calculated using the following equation:

SOR=
$$\frac{(AOR)^*(C_{S20})}{(\alpha)^*\{\beta^*C_S\text{-}C_W\}^*(1.024)^{T\text{-}20}}$$

Where:

- α Oxygen transfer wastewater, oxygen transfer tapwater
- β Wastewater saturation value, tap water saturation value
- T Effect of temperature on oxygen saturation value
- Ω effect of pressure on oxygen saturation value
- C_S dissolved oxygen concentration at saturation in clean water
- C_W minimum dissolved oxygen concentration in aeration basin
- C₅₂₀ concentration at saturation standard conditions of pressure and temperature

Oxygen requirements were analyzed for each basin. To determine the AOR and the SOR in each basin, it is necessary to first estimate the amount of BOD reduction occurring in that basin.

BOD Reduction

BOD reduction in each basin was estimated using a first order removal rate model developed by Wehner and Wilhelm for flow through conditions for reactors exhibiting plug flow and complete mix¹ conditions. First order removal rates appropriate for facultative and partially mixed aerated lagoons were selected for the Blue Lake Wastewater Treatment Facility (BLWWTF) and corrected for temperature. The detention time, reaction rates, and resulting BOD reduction for each pond for summer and winter seasons are summarized in Table 1 on the following page.



M97 No Me Barchool Ed Cyty Waternager Engineering Treatment Disposal and Reuse Aeration Analysis Blue Lake WWTF, Impact of Brewery Effluent November 7, 2013
Page 3 of 5



Mr. John Berchtold, City Manager **Aeration Analysis Blue Lake WWTF, Impact of Brewery Effluent** November 7, 2013 Page 4 of 5

	Table 1									
		BOD Reduction								
Blue Lake Wastewater Treatment Facility, Blue Lake, CA										
,	V a leerna a	Summer (0.14 MGD) ¹	Winter (0.40 MGD)							

	Volume	Sum	mer (0.14 M	GD) ¹	Winter (0.40 MGD)			
Basin		DT^3 $(K_st)^4$		Removal	DT	I I/ 15	Removal	
	(MG ²)	(days)	(N _S t) [∓]	(%)	(days)	K _w t ⁵	(%)	
1A	0.91	6.51	1.3	62	2.28	0.36	40	
1B	2.25	16.00	3.2	83	5.63	0.90	52	
2	1.35	9.61	1.9	70	3.36	0.53	40	
3	1.28	9.15	1.83	70	3.20	0.51	40	
4	2.66	19.0	3.8	88	6.65	1.00	45	

- 1. MGD: million gallons per day
- 2. MG: million gallons
- 3. DT: detention time
- 4. k_s : First order reaction rate constant at 16 Degrees C = 0.20
- 5. k_w : First order reaction rate constant at 12 Degrees C = 0.16

NH3-N Reduction

The oxygen demand exerted by the oxidation of Ammonia Nitrogen (NH $_3$ -N) was included in the analysis of oxygen requirements by assuming 4.6 lbs of oxygen required for each 1.0 lb. of NH $_3$ -N removed (4.6 lbs O $_2$ per 1.0 lb of NH $_3$ -N is based on the stoichiometry of nitrification). This assumption is conservative because NH $_3$ -N removal in a lagoon system also includes gaseous ammonia stripping and nitrogen assimilation in plant mass.

The rate of removal was estimated using an empirically derived first order equation which estimates the rate of nitrification for various lagoon detention times and temperatures.²

Supplemental Aeration Requirement

Estimated power requirements are based on the calculated SOR (lb. O_2 /day) divided by the standard aeration efficiency (SAE) of the aerators (lb O_2 /HP-hr). Typical surface axial aerators have SAEs which range from 2.0-3.5 lbs O_2 /hr³. The recently installed aerators at BLWWTF and any new aerators were assumed to have an SAE of 2.5 lbs O_2 /hr.

The aeration requirements summarized in the Table 2 (on the following page) are based on simulations of summer conditions (May- October) in the lagoon system. Summer conditions were determined to be the limiting condition for aeration requirements in Basin 1A and 1B because higher BOD loading requires increasing the amount of BOD oxidized in these basins.



² 1983, EPA Technical Report, Design Manual Municipal Wastewater Stabilization Ponds

³ 1988, Water Pollution Control Federation, <u>Aeration: Manual of Practice FD-13</u>

Table 2 Aeration Requirements (SOR) Blue Lake Wastewater Treatment Facility, Blue Lake, CA								
		Conditions	With Proposed Brewery Loadin					
	lbs. O₂/day	HP	lbs O2/day	HP				
1A	754	12.6	1,070	17.8				
1B	425	7.1	550	9.2				
Total	1,179	19.7	1,620	27				

Conclusion

The BLWWTF has three, 5 HP aerators in Basin 1A which supply more than the SOR required for existing conditions. Basin, 1B operates as a facultative lagoon with a much lower loading rate than Pond 1A. Performance data for existing conditions suggests that excess oxygen supplied in Pond 1A and oxygen transfer (wind and waves) occurring at the surface through natural processes provide sufficient oxygen to achieve the required effluent quality. However, with the addition of the new brewery loading, the existing aeration equipment and natural aeration will be insufficient to treat the projected loading without affecting effluent quality.

The increased oxygen demand is estimated to require an additional 5.2 HP and 2.1 HP in 1A and 1B respectively. Because of the higher loadings exerted on 1A and the first part of Basin 1B additional supplemental aeration is recommended. The total demand in 1A and 1B with the new brewery loading translates to a total aeration requirement of 27 HP.

Recommendations

Allowing an increase in MRB loading will require increasing the total aeration capacity of the BLWWTF by $440 \, \text{lbs-O}_2/\text{day}$. This amount of air can be supplied by installing aeration equipment to provide a minimum of 7.3 HP. The analysis also shows that the system has an existing oxygen deficit of 282 lbs-O₂/day (equal to 4.7 HP) when natural aeration is discounted from the facility.

Existing aeration equipment is comprised of three 5 HP surface aerators. New aeration equipment will need to be located in Pond 1-A and Pond 1B, in areas that are shallower than the location of the current aerators. Scour of the lagoon bottom is a concern and the depth at each new aerator location should be examined more closely. It is also recommended that any new aeration equipment match the type and size of the existing aerators resulting in two 5 HP aerators. Proposed aerator locations are presented on Figure 1. The amount of oxygen supplied by the two aerators will offset the City's reliance on natural aeration by the equivalent of 2.7 HP.

Budgetary cost for purchase and installation of two surface aerators is summarized in Table 3 on the following page. The costs are based on estimates obtained from the manufacturers of the existing aerators; the Aqua-Lator (511) manufactured by Siemans, and the Aqua Jet manufactured by Aqua-Aerobics.



Mr. John Berchtold, City Manager **Aeration Analysis Blue Lake WWTF, Impact of Brewery Effluent** November 7, 2013 Page 6 of 5

Table 3 Additional Aerators–Engineer's Opinion of Probable Cost Blue Lake Wastewater Treatment Facility, Blue Lake, CA						
Contractor overhead, profit, bonding, insurance	\$11,000					
Aeration Equipment ¹	\$18,000					
Cable	\$1,000					
Installation	\$6,000					
Electrical	\$20,000					
Subtotal	\$56,000					
Contingency	\$9,000					
Engineering Procurement	\$12,000					
Total	\$77,000 ²					
1. Manufacturers quotes plus 20%						
2. Taxes and fees not included.						

The City has agreed in concept to a cost sharing arrangement. As a starting point for further discussion, approximately 27% of the oxygen provided by the two 5 HP exceeds the projected oxygen required for the MRB loading. The additional aeration will augment the natural aeration, providing a more reliable facility than the current configuration.

Power Requirements

See Attachment 2, Electrical Review and Response prepared by Richard Sample Engineering.

References

Metcalf and Eddy. (1972). Wastewater *Engineering: Collection, Treatment, Disposal*. New York, NY:McGraw-Hill.

Water Pollution Control Federation. (1988). *Aeration: Manual of Practice FD-13*. Alexandria, VA:WPCF.

U.S. Environmental Protection Agency. (1983). *EPA Technical Report, Design Manual Municipal Wastewater Stabilization Ponds*. Cincinnati, OH:EPA.

STAN



AVAILABLE CONTRACTOR OF THE PARTY OF THE PAR

I.D. No. 1B811290HUM RDER No. RI-2012-005 SELF MONITERING REPORT
DISCHARGER: CITY OF BLUE LAKE

DATE: January 7th, 2013

For the Months of January thru December, 2012

REQUIREMENTS COMPLIANCE SUMMARY

	INFL	UENT	EFFL	UENT	EFFL	UENT	EFFLUENT		EFFLUENT EFFL		EFFLUENT		Γ
	QUAR	TERLY	DA	ILY	MON.	THLY	MONTHLY		MONTHLY		MONTHLY		′
					B.O.D	N.F.R			COLI	FORM			
					Б.О.D	N.F.K	SETILEABL	E SOLIDS	MPN	MPN	1	NITROGEN	1
			FLO	WC	mg/L	mg/L			100 ml 100 Ml				
	B.0.D	N.F.R	MGD	MGD	MAX 80	MAX 80	mg/L	mg/L	MAX	MEDIAN	NITRATE	NITRITE	TOTAL
	mg/L	mg/L	MAX	MEAN	MEAN SO	MEAN 5	MAX 0.2	MEAN 0.	230	23			
IIONTH													
JAN	100	130	1.863	0.561	16	44	<.1	<.l	4.5	<1.8			
FEB	91	110	0.700	0.309	14	23	<.I	<.l	<1.8	<1.8			
MAR	440	470	1.175	0.538	33	41	<.l	<.l	2.0	2.0			
APR	110	SO	1.263	0.589	17	22	<.l	<.1	<1.8	<1.8			
MAY	130	130	0.3S2	0.184	ND	11	<.1	<.l	<1.8	<1.8			
JUN	240	110	0.526	0.225	26	41	0.2	<.1	1600	20	ND	ND	2.6
JUL	220	140	0.258	0.128	20	40	<.1	<.1	2.0	<1.8	ND	ND	4.4
^UG	183.75	119.5	0.146	0.111	21/17.8	SI/16.3	<.l	<.1	3SO	6.S	ND	ND	4.8
₹ P	350	240	O.IIS	0.087	27	16	<.1	<.l	<1.8	<1.8	0.52	ND	4.6
OCT	260	280	0.364	O.ISI	3.9	1.8	<.l	<.1	<1.8	<1.8	0.39	ND	7.4
NOV	180	160	0.470	0.269	7.S	4.3	<.1	<.1	<1.8	<1.8	0.50	ND	6.6
DEC	49	S0	0.631	1.100	14	11	<.l	<.l	2.0	<1.8	2.70	0.59	6.9

B.O.D. N.F.R. & NITROGEN TESTS TAKEN ON:

/3/12	0 /1 /10					JUL	AUG	SEP	OCT	NOV	DEC
	2/1/12	3/6/12	4/11/12	5/29/12	6/18/12	7/19/12	8/2/12	9/13/12	10/4/12	11/1/12	12/6/12
./3/12	2/1/12	3/6/12	4/11/12	5/29/12	6/18/12	7/19/12	8/2/12	9/13/12	10/4/12	11/1/12	12/6/12
					1/iJ./U	"//1912J] 1	8/Zf.ll,	9/13fQ.	.JJJ/1'!/12	11/i/U	12/14/12
1/13./0 //19123 }							8-7 to 8-13				
Т							8-7 to 8-13				
							8/23/12				
						1/iJ./U	1/iJ./U "//1912J}l	1/iJ./U "//1912J]1 8/Zf.1l, 8-7 to 8-13 8-7 to 8-13 8/23/12	1/iJ./U "//1912J]1 8/Zf.1l, 9/13fQ. 8-7 to 8-13 8-7 to 8-13	1/iJ./U "//1912J]I 8/Zf.ll, 9/13fQJJJ/l'll2 8-7 to 8-13 8-7 to 8-13 8/23/12	1/iJ./U "'//1912J]1 8/Zf.1l, 9/13fQJJJ/1'/12 11/i/U 8-7 to 8-13 8-7 to 8-13 8/23/12

OTES: *Extra tests taken for local limits study. ** Test taken to determine if rock filter still needed.

equired Nitrogens testing started in June

sults from average of all tests taken

I.D. No. 1B811290HUM ORDER No. 94-28 Self Monitoring Report
DISCHARGER: CITY OF BLUE LAKE

FOR MONTHS OF: Jan-Dec 11

REQUIREMENTS COMPLIANCE SUMMARY

	INFLUENT		EFF	LUENT	EFF	LUENT	EFF	LUENT	EFFL	.UENT
	QUARTERLY		DA	DAILY		MONTHLY		THLY	MONTHLY	
			1 (1						COLI	FORM
		- 1	2		B.O.D	N.F.R	SETII FABI	E SOLIDS	MPN	MPN
			FL	OW	mg/L	mg/L	OL HELMO!		100 ml	100 MI
	B.O.D	N.F.R	MGD	MGD	MAX 80	MAX 80	mg/L	mg/L	MAX	MEDIAN
	mg/L	mg/L	MAX	MEAN	MEAN SO	MEAN SO	MAX 0.2	MEAN 0.1	230	23
MONTH										
JAN	160	110	0.784	0.303	17	28	<.1	<.1	<1.8	<1.8
FEB	81	110	0.6S1	0.294	s	22	<.1	<.1	<1.8	<1.8
MAR	130	90	0.922	O.S72	20	2S	<.1	<.1	<1.8	<1.8
APR	130	1 10	0.6S1	0.338	8	12	<.1	<.1	<1.8	<1.8
MAY	170	180	0.202	0.164	19	8	<.1	<.1	<1.8	<1.8
JUN	260	140	0.2\$4	O.IS	11	7	<.1	<.1	<1.8	<1.8
JUL	240	180	0.184	0.101	12	33	<.1	<.1	<1.8	<1.8
"'IG	240	220	0.118	0.104	10	13	<.1	<.1	<1.8	<1.8
. P	340	370	0.113	0.093	27	8	<.1	<.1	<1.8	<1.8
ОСТ	140	140	0.671	0.198	3.9	10	<.1	<.1	<1.8	<1.8
NOV	380	260	0.408	0.241	6.S	11	<.1	<.1	<1.8	<1.8
DEC	190	180	0.288	0.191	8.8	33	<.1	<.1	<1.8	<1.8

B.O.D & N.F.R TESTS TAKEN ON:

FIRST Q	UARTER	SECOND (QUARTER	THIRD C	UARTER	FOURTH QUARTER	
	Ning and						
Jan 5 2011	INFLUENT	Apr 8 2011	INFLUENT	Jul 1 2011	INFLUENT	Oct 19 2011	INFLUENT
Feb 9 2011	INFLUENT	May 6 201	INFLUENT	Aug 5 2011	INFLUENT	Nov 14 2011	INFLUENT
Mar 3 2011	INFLUENT	Jun 3 2011	INFLUENT	Sep 7 2011	INFLUENT	Dec 13 2011	INFLUENT
May Series					With Earlies		
Jan 5 2011	EFFLUENT	Apr 8 2011	EFFLUENT	Jul 12011	EFFLUENT	Oct 19 2011	EFFLUENT
Feb 9 2011	EFFLUENT	May 6 201:	EFFLUENT	Aug 5 2011	EFFLUENT	Nov 14 201	EFFLUENT
Mar 3 2011	EFFLUENT	Jun 3 2011	EFFLUENT	Sep 7 2011	EFFLUENT	Dec 13 201	EFFLUENT

_...,11 PREPARED BY: GLENN BERNALD . CHIEF PLANT OPERATOR DATE: — Jan 9 2042 ——— '



Blue Lake Wastewater Treatment System

Existing Loading Prepared By SMF 11/6/2013 Summer Conditions Basin 4 **Section 1: Process Parameters** AAF Design Flow 0.14 MGD 530 m³/day Influent BOD5 1 mg/l 2 lb/day 1 kg/day Design Effluent BOD5 1 mg/l 1 lb/day O kg/day Influent NH₃-N 18 mg/l 21 lb/day 10 kg/day Design Effluent NH₃-N 14 mg/l 16 lb/day 7 kg/day Basin Temperature (Max) 65 degrees F 18 degrees C Elevation 100 ft MSL 30 m MSLSection 2: Basin Geometry Pond 4 $10,069 \text{ m}^3$ Total Volume 2.66 MG HAT 19.00 davs@ ADWF Section 3: Aeration Requirements **AOR Calculation** BOD₅ Removed 1 lb/day O kg/day NH₃-N Removed 5 lb/day 2 kg/day 2.5 lb 02/lb BOD5 2.5 kg 02/kg BOD5 4.6 kg 0₂/kg NH₃-N 4.6 lb 0₂/lb NHrN Total AOR to system 24 lb O2/day 11 kg O₂/day **SOR Calculation** SOR = (AOR) • (Cs2o) (a)*(jJ • C₅ - Cwl • (1.024) T-20 Where: 0.80 -9.37 Cs = 0.95 -2.0 b =Cw =1.03 Cs20 = 9.09 t =1.00 Temp = 18 W = Therefore: SOR = 41 lb 02/day 19 kg 02/day SOR = 2 lb 0₂/hr/basin 1 kg 0₂/hr/basin Type of Aerator Aerator 2.5 lb 02/Hp-hr SAE of Aeration System 1.5 kg 02/kW-hr Existing aerators 0.7 Hp/basin Aeration Power Required 0.5 kW/basin One additional Section 4: Mixing System Design 1.0 W/m^3 Design Mixing Intensity 5 Hp/MG Mixing Power Required 13.3 Hp/basin 9.9 kW/basin

^{*} indicates assumed values

Blue Lake Wastewater Treat Existing Loading Summer Conditions Pond 3 Section 1: Process Param	·		Prepared By SMF 11/6/2013			
AAF Design Flow	0.14 MGD			530 m³/day		
Influent BOD5	5 mg/l 6 lb/da	ny	3 kg/day			
Design Effluent BOD ₅	1 mg/l 2 lb/da			1 kg/day		
Influent NH ₃ -N	21 mg/l 25 lb/da	•				
Design Effluent NHrN	18 mg/l 21 lb/da	•		11 kg/day 10 kg/day		
Basin Temperature (Max)	65 degr			18 degrees C		
Elevation	100 ft MS	SL		30 m MSL		
Section 2: Basin Geometr	у					
Pond 3 Total Volume	1.28 MG			4,845 m ³		
HAT	9.15 <u>days</u> €	ADWF				
Section 3: Aeration Requirements AOR Calculation	rements					
BOD ₅ Removed	4 lb/da	у		2 kg/day		
NH ₃ -N Removed	4 lb/da	у		2 kg/day		
	2.5 lb 02	/lb BOD5		2.5 kg 02/kg BOD5		
	4.6 lb 02	2/lb NH ₃ -N		4.6 kg 0 ₂ /kg NH ₃ -N		
Total AOR to system	27 lb O ₂	₂ /day		12 kg Oday		
SOR Calculation						
SOR=	(AOR) • (C _{s20}) (a)'({J •c cwJ • rt.02	<i>4)T-</i> 2Q				
Where:						
a =	0.80 _	Cs =	9.37			
b =	0.95 -	Cw=	2.0			
t = W =	1.03 1.00	Cs20 = Temp =	9.09 18			
Therefore:						
SOR =	46 lb 02	2/day		21 kg 0 ₂ /day		
SOR =	2 lb 02	n/hr/basin		1 kg 02/hr/basin		
Type of Aerator	Aera	tor				
SAE of Aeration System	2.5 lb 02 Existing aerators	2/Hp-hr		1.5 kg 02/kW-hr		
Aeration Power Required	0.8 Hp/b One additional	asin		0.6 kW/basin		
Section 4: Mixing System						
Design Mixing Intensity	5 Hp/N	1G		1.0 W/m ³		
Mixing Power Required	6.4 Hp/b	asin		4.8 kW/basin		

Existing I Summer Basin 2	e Wastewater Treat Loading Conditions 1: Process Param	·			Pre	pared By SMF	11/6/2013
AAF	Design Flow	0.14	MaQ			530 m³/da	y
	Influent BOD ₅	15	mg/l				
Des	sign Effluent BOD ₅		lb/day			8 kg/da	у
200			mg/l lb/day			3 kg/da	У
	Influent NH₃-N		mg/l lb/day			12kg/do	
Des	ign Effluent NH₃-N		mg/l			13kg/da	у
		25	lb/day			11 kg/da	у
Basin T	Basin Temperature (Max) 65 degrees F					18 degre	es C
	Elevation	100	ft MSL			30 m MS	SL.
Section	2: Basin Geometr	у					
Pond 2	Total Volume	1.35	MG			5,110 m ³	
	HRT	9.61	davs@ AD\	ΝF			
Section	3: Aeration Requir AOR Calculation	ements					
	BOD₅ Removed	12 lb/day				5 kg/da	v
	NH ₃ -N Removed		lb/day			2 kg/da	
		2.5	lb 02/lb B	OD.		2.5 kg 00	/ka BOD
			lb 0 ₂ /lb N			2.5 kg 02 4.6 kg 02	/kg NH ₃ -N
То	tal AOR to system	51	lb O₂/day			23 kg O ₂	/day
	SOR Calculation						
	SOR=	(AOR)•(0 (aJ·rp·cs- C)		20			
	Where:						
		0.80	-	C.=	9.37		
	b =	0.95		Cw=	2.0		
	t = W =	1.03 1.00		Cs20 = Temp =	9.09 18		
		50		r			
	Therefore: SOR =	87	lb 02/day			40 kg 02	/day
	SOR =		lb 02/hr/b			-	/hr/basin
	Type of Aerator		Aerator				
SAE o	of Aeration System		lb 02/Hp-	hr		1.5 kg 02	'kW-hr
Aeratio	n Power Required		Hp/basin			1.1 kW/ba	asin
Section	4: Mixing System	One additic1n Design	al				
Desig	gn Mixing Intensity	5	Hp/MG			1.0 W/m ³	
	g Power Required					5.0 kW/ba	aein
IVIIXIN	ig rowei kequired	0.8	Hp/basin			J.U KVV/D	11162

Blue Lake Wastewater Treat Existing Loading Summer Conditions Pond 1B Section 1: Process Param	·	Prep	ared By SMF 11/6/2013				
AAF Design Flow	v 0.14 MGD			530 m³/day m³/day			
Influent BOD Design Eflluent BOD	103 lb/dav			47 kg/day			
Influent NH ₃ -N	18 lb/day			8 kg/day			
Design Effluent NH ₅ -N	37 lh/day			17 kg/day			
	29 lb/day			13 kg/day			
Basin Temperature (Max) 65 degrees	s F		16 degrees C			
Elevation	100 It MSL			30 m MSL			
Section 2: Basin Geomet				55 52			
Pond 1B Total Volume	e 2.25 MG			B,517 m ³			
HR	T 16.00 <u>dw@ Al</u>	DWF_					
Section 3: Aeration Requ AOR Calculation							
BOD5 Remove	d B5 lb/day	39 kgfday					
NH ₃ -N Remove	d 8 lb/day	8 lb/day					
	25 lb Oi!b 4.6 lb O;!"lb			25 kg O;!"kg BOD ₅ 4.6 kg 02:"kg NHs-N			
Total AOR to system	n 248 lb 0,,/da	ny		113 kg 0-).day			
SOR Calculation	n						
SOR =	(AOR} " IC,) (a)' /JJ • C,.CJ • (1.024	!) •,					
Where:							
a:	= 0.30 •	C _=	9.78				
b:	= 0.95.	Cw=	2.0				
I= W l		Cr® = Temp =	9.09 16				
	_ 1.00	remp =	10				
Therefore: SOR :	= 425 lb 0 ₂ /da	21/		193 kg O day			
SOR:		•		8 kg 02'hr/basln			
Type of Aerato				J			
SAE of Aeration System		p∙hr		1.5 kg O;!"kW-hr			
Aeration Power Required				5.3 kW/basin			
Section 4: Mixing System	One additional Section 4: Mixing System _Design						
Design Mixing htensity	y 5 HpfMG			1.0 W/m ³			
Mixing Power Required	d 11.3 Hp/basi	11.3 Hp/basin					

Blue Lake Wastewater Treatment System

Prepared By SMF **Existing Loading** Summer Conditions 116/2013 Basin 1A Section 1: Process Parameters AAF Design Flow 0.14 MGD 530 m³/day Influent BODs 231 mg/l 270 lb/day 123 kg/day Design Effluent BOD₅ 88 mg/l 103 lb/day 47 kg/day Influent NH₃-N 35 mg/l 41 lb/day 19 kg/day Design Effluent NH₃-N 32 mg/l 37 lb/day 17 kg/day Basin Temperature (Max) 18 degrees C 65 degrees F Elevation 100 ft MSL 30 m MSL Section 2: Basin Geometry Pond 1A 3,445 m³ Total Volume 0.91 MG HRT 6.51 davs@ ADWF Section 3: Aeration Requirements **AOR Calculation** BOD₅ Removed 167 lb/day 76 kg/day NH₃-N Removed 2 kg/day 4 lb/day 2.5 lb O:flb BOD₅ 2.5 kg O:fkg BOD₅ 4.6 lb 02/lb NH3-N 4.6 kg 02/kg NH3-N Total AOR to system 436 lb O2/day 198 kg O2/day **SOR Calculation** SOR = (AOR) • (Cs20) (a)*{{J°C,- Cw} (1.024)'-' 0 Where: 0.80 * Cs = 9.78 0.95 Cw= 2.0 1.07 Cs20 = 9.17 1.00 Temp = 16 W = Therefore: SOR = 754 lb 02/day 343 kg 02/day 31 lb 02/hr/basin 14 kg 02/hr/basin SOR = Type of Aerator Aerator SAE of Aeration System 2.5 lb 02/Hp-hr 1.5 kg O₂/kW-hr Existing aerators Aeration Power Required 12.6 Hp/basin 9.4 kW/basin One additional Section 4: Mixing System Design Design Mixing Intensity 5 Hp/MG 1.0 W/m3 Mixing Power Required 4.6 Hp/basin 3.4 kW/basin



Blue Lake Wastewater Trea Existing Loading Winter Conditions Basin 4 Section 1: Process Parar	·	Prepared By SMF	1612013			
Peak Daily Flow Influent BOD ₅						
	28 lb/day	13 kg/day				
Design Effluent BODs	4 mgfi 0 lb/day	0 kg/dov				
Influent NH ₃ -N		0 kg/day				
Design Effluent NH₃-N	29 lb/day 8 mg/l	13 kg/day				
· ·	26 lb/day	12 kg/day				
Basin Temperature (Max)	54 degrees F	12 degrees	С			
Elevation	100 ft MSL	30 m MSL				
Section 2: Basin Geometr	у					
Pond4 Total Volume	2.66 MG	10,069 m;				
HRT	6.65 days @MMWWF					
AOR Calculation						
DOD D	00 -1	40 lenfeless				
BOD ₅ Removed NH ₃ -N Removed	•	13 kgfday 2 kg/day				
141 314 Nemoved Sibiday 2 kg/day						
	2.5 lb Oi/lb BODs 46 lb Oi/lb NH ₃ -N	2.5 kg OVI <g 4.6 kg Oi/k.Q</g 				
Total AOR to system	85 lb 02'day	39 kg 02'da	У			
SOR Calculation						
SOR -	(AOR) • !C.,.J (a)"(/J " C,- C.,,) " (1 024) y"•					
	(4) (70 - 6) - 61,111 (1 - 621)					
Where:	0.80 . C.=	10.71				
(1	0.95 . Cw :::	2.0				
	1.18 Co20 =	9.09				
n -	1.00 Temp =	12				
Therefore:						
SOR =	•	65 kg Di/da	-			
SOR =	6 lb 0 ₂ fhrfbasin	3 kg 0₂fhr	/basin			
Type of Aerator	Aerator					
SAE of Aeration System		1.5 kg Oi/kV	V-hr			
Aeration Power Required	Existing aerators 2.4 Hp/basin One additional	1.8 kW/basi	n			
Section 4: Mixing System						
Design MiXing Intensity	5 Hp/MG	1.0 W/m ³				
Mixing Power Required	I 13.3 Hp/basin	9.9 kW/basi	n			
•						

Existing Loading

Winter Conditions 1116/2013 Basin 3 Section 1: Process Parameters Peak Dally Flow Innuent BOD 0.4 MGD 14 mg/l 47 lb/day 21 kg/day Design Effluent BOD₅ 8 mg/l 28 lb/day kg/day Influent NH₃-N 9 mg/l 31 lb/day 9 mg/l 14 kg/day Design Effluent NH:;N 29 lb/day 13 kg/day 54 degrees F Basin Temperature (Max) 12 degrees C Elevation 100 ft MSL 30 rn MSL Section 2: Basin Geometry Pond 3 Total Volume 1.28 MG 4,845 m³ HRT 3.20 days @MMWWF AOR Calculati on BOD₅ Removed 19 lb/day 8 kg/day NH₃-N Removed 2 lb/day 1 kg/day 2.5 lb O;illb BOD₅ 2.5 kg O;ilkg BOD5 4_6 lb O lb NH3-N 4.6 kg O:iJkg NH₃-N Total AOR to system 56 lb O:ifday 25 k.g O;ilday SOR Calculation SOR z (AOFI) • (C ,, .) (a)'(fl " C, ·CN) '(1-024)'''⁰ Where: 0.80. (1 c.=10.71 (J0.95 • Cw: 2.0 c20= 9.09 7 1.18 D Temp = 1.00 12 Therefore: SOR = 94 lb 0₂/day 43 kg O'lfday SOR = 4 lb 02'hr/basin 2 kg O:i/hr/basln Type of Aerator Aerator SAE of Aeration System 15 kg O:kW-hr 2.5 lb O₂/Hp-hr Existing aerators Aeration Power Required 1.6 Hp/basin - 1-2 kW/basin One additional Section 4: Mixing System Design Design Mixing Intensity 5 Hp/MG 1.0 W/m^3 Mking Power Required 6.4 Hp/basin 4.8 kW/basin

Prepared By SMF

Existing Loading Winter Conditions Prepared By SMF 11/6/2013 Basin 2 Section 1: Process Parameters 0.4 MGD 23 mg/l Peak Dally Flow Influent BOD₀ 77 lb/day 35 kg/day Design Effluent BOD.s 14 mg/l 47 lb/day 21 kg/day InHuent NH:r-N 10 mg/l 33 lb/day 9 mg/! 15 kg/day Design Effluent NHTN 31 lb/day 14 kg/day Basin Temperature (Max) 54 degrees F 12 de.grees C 100 ft MSL Elevation 30 m MSL Section 2: Basin Geometry Pond 2 1.35 MG $5,110 \text{ m}^3$ Total Volume HRT 3.36 days @MMWWF **AOR** Calculation BOD Removed 30 lb/day 14 Kgfday NHJ-N Removed 2 lb/day 1 kg/day 2.5 lb O:iJlb BOD5 2.5 kg O,jkg BOD5 4.6 lb O lb NH₃·N 4.6 kg Oz/kg NH₃-N 38 kg O,Jday 84 lb O/day Total AOR to system SOR Calculation SOR • (AOR) '(C.,.) («J"({J•C,-C,.J•(1024/;20 Where: 11 0.80. C _= 10.71 $C_w =$ 0.95. 2.0 fJ 1.18 $C_020 =$ 9.09 fl 1.00 Temp = 12 Therefore: 142 lb Oz/day SOR= 64 kg /day 6 lb 02'hr/basin SOR = 3 kg 0₂/hr/basin Type of Aerator Aerator 1.5 kg O2/kW-hr SAE of Aeration System 2.5 lb 02/Hp-hr Existing aerators Aeration Power Required 2.4 Hp/basin 1.B kW/basin One additional Section 4: Mixing System Design Design Mixing Intensity 5 Hp/MG 1.0 Wlm Mixing Power Required 6.8 Hp/basin 5.0 kW/basin

Existing Loading Prepared By SMF Winter Conditions 1115/2013 Basin 1B Section 1: Process Parameters Peak Daily Flow $0.4~\mathrm{MGD}$ $1,514 \text{ m}^3 \text{ tday}$ Influent BODs 48 mg/l 160 23 mg/l 73 kg/day Design Effluent BOD₅ 77 lb/day 35 kg/day 11 mg/l 35 lb/day Influent NH:rN 16 kg/day Design Effluent NH₃-N 10 mg/l 33 lb/day 15 kg/day Basin Temperature (Max) 54 degrees F 12 degrees c Elevation 100 ft MSL 30 m MSL Section 2: Basin Geo.metry Pcmd 16 $8,517 \text{ m}^3$ Total Volume 2-25 MG 5.63 days @MMV\11/VF HRT AOR Calculation BOD_5 Removed 83 lb/day 38 kg/day NH₃-N Removed 2 lb/day 1 kg/day 2.5 lb Oz/lb BOD₅ 2.5 kg O:ifkg 60D5 4.6 lb O;illb NH₃N 4.6 kg O:zlkg NH₃-N 99 kg O.jday Total AOR losystem 218 lb O:day SOR Calculation SOR • (AOR)'(C,,.) (IX}"{{J " C,·Cw) " (1.02)'°" Where: 0.80 . 10.71 п C .= 0.95 . Cw = 2.0 1.18 C io = 9.09 1.00 Temp = 12 Therefore SOR = 366 lb O:zlday 166 kg 0-lfday 15 lb O:ifhr/basln SOR = 7 kg O;lhibas n Type of Aerator Aerator 2.5 lb QHphr 1.5 kg O:zlkW-hr SAE or Aerat!on System E.xJsting aerators Aerauon Power Required 6.1 Hp/basin 4.5 kW/basin One additional Section 4: Mixing System Design Design Mixing Intensity 5 Hp/MG 1.0 Wim^3 6.4 kW/basin Mixing Power Required 11.3 Hp/basin

Existing Loading

11/6/2011 Winter Conditions Basin 1A RevisJon: Section 1: Process Parameters AWWF Peak Flo1ign Flow $0.40~\mathrm{MGD}$ 1,514 m³fday hfluent BOD₆ 80 mg/l 270 lbfday 123 kg/day Design Effluent BOD₅ 46 mgll 160 lb/day 73 kg/day Influent NH:rN 11 mg/l 37 lb/day 17 kgfday 106 mg/l Design Effluent NH,-N 35 lb/day 16 kgfday Basin Temperature (Max) 54 degrees F 12 degrees C 100 ft MSL 30 m MSLElevation Section 2 Pond 1A Basin Geometry Total Volume 0.91 MG 3.445 rn³ HRT 2.28 days @MMWWF **AOR Calculation** BOD₅ Removed 110 lb/day 50 kg/day NH₃-N Removed 2 lbfday 1 kg/day 25 lb 02'1b BODs 2.5 kg O;/kg BOD5 4.6 lb02'fb NH:rN 4.6 kg Otkg NH3-N 282 lb Otday 128 kg 02'day Total AOR to system **SOR Calculation** SOR: (AOR) "(Cm) (a)'(fJ " C, ·Cw) '(1.024/'" Where: 0.80 . C,= (\ 10.71 *C*,.,= (J 0.95 . 2.0 **2**0 "' 9 17 7 1.17 11 1.00 Temp= 12 Therefore: SOR = 479 lb Ofday 218 Kg 0-jday SOR = 20 lb 0-thrlbasin 9 kg Oi/hr/bash Type or Aerator Aerator 2.5 lb OiJHp-hr 1.5 kg 02/kW-hr SAE of Aeration System Existing aerators Aeration Power Required 8.0 Hpfbasin 5.9 kW/basin One additional Section 4: Mixing System DesIgn 3.0 Wfm³ Deign Mixing Intensity 15 HpfMG 10.2 kW/basin Muong Power Required 13.7 Hpfbasin

Prepared By SMF

WITH BREWERY SUMMER

Blue Lake Wastewater Treatment System Brewery Loading Summer Conditions Basin 4

Prepared By SMF Revision:

Section 1: Process Parameters

Section 1	: Process Parameter	S			
AAF	Design Flow	0.14 <u>days@</u> A0 0.4 days@			530 m³/day
	Influent B0D ₅	2 mg/l			
D	F#I POD1	2 lb/day			1 kg/day
Desi	ign Effluent BOD₅ <1	mgfl lb/day			O kg/day
	Influent NH3-N	18 mgfl			O kg/day
D:	Effice of All look	lb/day			O kg/day
Desi	gn Effluent NH:rN	14 mg/l 16 lb/day			7 kg/day
		•			r kg/day
Basin Te	emperature (Max)	65 degrees	F		18 degrees C
	Elevation	100 ft MSL		•	30 m MSL
Section 2 Pond4	2: Basin Geometry				
POHU4	Total Volume	2.66 MG			10,069 m ³
	HRT	19.00 davs@ A	OWF		
	AOR Calculation				
	900 ₅ Removed	2 lb/day			1 kg/day
	NH ₃ -N Removed	- 16 Iblday			-7 Kg/day
		•			3 ,
		2.5 lb 02'1b			2.5 kg O,lkg BOD ₅
		4.6 lb Oiflb I	NR3-N		4.6 kg Oi/k.g NHrN
Section 3	al AOR to system 3: Aeration Requireme SOR Calculation	-70 lb OJda ents	ay		-32 kg 02'day
	SOR	(AOR} '(C,,,.)			
	rar	fp.c,-c,J.('OU)	7- F		
,	Where:				
		0.80 _	C =	9.37	
	(1	0.95 _	C,,=	2.0	
	T =	1.03	Coio =	9.09	
	ri –	1.00	Temp =	18	
	Therefore:				
	SOR =	-121 lb Oz/da	у		-55 kg OiJday
	SOR =	-5 lbO/hr	/basin		-2 kg 02'hrlbasin
	Type of Aerator	Aerator			
SAE of	f Aeration System	2.5 lb 02/H _l	1.5 kg 02/kW-hr		
Aeration	E>- n Power Required -2.0	isting aerators Hp/basin	-1.5 k.Wlba.sin		
Section 4	On 1: Mixing System Des	e additlonal ign			
	5 - /	<u> </u>			
Desig	n Mi> <ing intensity<="" td=""><td>5 Hp/MG</td><td></td><td></td><td>1.0 Wlm³</td></ing>	5 Hp/MG			1.0 Wlm ³
Mixin	g Power Required	13.3 Hp/bas	in		9.9 kW/basin
		- 1			

Blue Lake Wastewater Treatment System

Prepared By SMF Brewery loading Summer Conditions Revision: Basin 3 Section 1: Process Parameters 0.14 davs@ AQWF 530 m³tday Design Flow AAF 0.4 days @MMWWF Influent BOD₅ 6 mg/l 7 Iblday 3 kglday Design Effluent BOD₅ 2 mg/l 2 Ibbay 1 kglday Influent NHrN 21 mgll 25 Iblday 11 kglday Design Effluent NH₃-N 18 mgll 21 lbbay 10 kglday Basin Temperature (Max) 65 degrees F 18 degrees C Elevation 100 ft MSL 30 m MSL Section 2: Basin Geometry_ Pond3 Total Volume 1.28 MG 4.845 m³ HRT 9.15 dava@ l>.DWF Section 3: Aeration Requirements AOR Calculation BOD₅Removed 2 kg/day 5 lb/day NHrN Removed 2 kg/day 4 lb/day 2.5 lb 02'lb BOD; 2.5 kg 02/kg BODs 4.6 lb Oilb NHrN 4.6 kg 02'k9 NHrN Total AOR to system 28 lb O?fday 13 kg Oiday SOR Calculation (AOR) -re'®} SOR = (a)"{P" C,- C,.J "(1.024)'.,. Where: 1'.1 -0.80 . C.= 9.37 C..= (1 095. 2.0 1 03 C.io "-9.09 1 00 Temp = 18 Therefore: 22 kg 0₂/day SOR = 49 lb 0₂/day 2 lb Ohr/basin 1 kg 07/hr/basin SOR= Type of Aerator Aerator SAE of Aeration System 2.5 lb O₂/Hp-hr 1.5 kg O/kW-hr Existing aerators Aeration Power Required 0.8 Hplbasin 0.6 kW/basin One aclditional Section 4: Mixing System Design 5 HpIMG 1.0 W/m³ Design Mixing Intensity Mixing Power Required 6.4 Hp/basin 4.8 kW/basin

Blue Lake Wastewater Treatment System					Prepared By SMF		
Brewery Loading Summer Conditions					Revision:		
Basin 2 Section 1: Process Param	atore						
					3		
AAF Design Flow Influent BOD		m@ AOWF ng/1			530 m ³ /day		
Design Effluent BODs		b/day ngfl			10 kg/day		
•		o/day			3 kg/day		
Inflµent NH:rN	25 m	ng/1 o/day			13 Kg/day		
Design Effluent NH:rN	21 n				13 Ng/day		
	25 II	o/day			11 kg/day		
Basin Temperature (Max)	65 d	legrees F			18 degrees C		
Elevation	100 f	t MSL			30 m MSL		
Section 2: Basin Geometry	/						
Pond2 Total voiurne	1.35 N	1G			5,110 1)1 ³		
					3,110 1)1		
HRT Section 3: Aeration Requir		avs@ ADWF					
AOR Calculation							
BOD ₅ Removed	15 lk	o/day			7 kg/day		
NHrN Removed	5 lk	5 lb/day			2 kg/day		
	25	lb O;lb BOI) ₅		2.5 kg O:zfkg BODs		
		b 0.zilb NH			4.6 kg O;!kg NH3-1		
Total AOR to system	59 lb	59 lb <i>O;iday</i>			27 kg O.,Jday		
SOR Calculatron							
SOR •	$(AOR) \cdot re$						
	$(a)'(JJ \bullet C, \cdot Cw)$						
Where:							
(I =	0.80	-	C _=	9.37			
(J	0.95 •		Cw =	2.a			
Т	1.03		$C_{020} =$	9.09			
n	1.00	-	Temp =	18			
Therefore:							
SOR =		O;iday			47 kg O;fday		
SOR =	. 4	4 lb Oifhr/basin			2 kg O;fhr basin		
Type of Aerato	. ,	Aerator					
SAE of Aeration System	2.5	2.5 lb 0_2 /Hp-hr			1.5 kg O:ifkW-hr		
Existing aerators				13 kW/basin			
Aeration Power Required	1.7 I One additional	Mp/basin			i.o Kvv/dasin		
Section 4: Mi>dng System							
Design Mixing Intensity	5 H	Hp/MG			1.0 W/m ³		
Mixing Power Required 6.8 Hp/basin					5.0 kW/bash		

Blue Lake Wastewater Treatment System

1 Brewery Loading Prepared By SMF Summer Conditions Basin 1B Section 1: Process Parameters 530 m /day AAF Design Flow 0.14 MGD Influent BOD₅ 117 mg/l 137 lb/day 62 kg/day Design Effluent BOD5 19 mg/l 22 lb/day 10 kg/day Influent NH₃-N 32 mg/l 37 lb/day 17 kg/day Design Effluent NH₃-N 25 mg/l 29 lb/day 13 kg/day Basin Temperature (Max) 65 degrees F 16 degrees C Elevation 100 ft MSL 30 m MSL Section 2: Basin Geometry Pond 1B Total Volume 2J15 MG 6.517 m^3 HRT 16.00 dal:'.!I@ .8!JWE **AOR** Calculation BOD₅ Removed 114 lb/day 52 kg/day NHrN Removed a lb/day 3 kg/day 2.5 lb 0_2 /lb BOD₅ 25 kgO:iJkg BODs 4.6 lb O}lb NHJ-N 4.6 kg 02/kg NHrN Section 3: Aeration Requirements Total AOR to system 321 lb OiJday 146 kg 02'day SOR Calculation SOR = (AOR) •(C"°) (a)"{fJ" C,- C,,J • (1.024) Where: C .= 9.78 0.80 -0.95 _ $C_{,,=}$ 2.0 (1 c. = 1.08 9.09 0 1.00 Temp = 16 Therefore: 550 lb 0_2 fday 250 kg Oif day SOR = $23 \text{ lb } 0_2/\text{hrfbas1n}$ 10 kg 0₂/hrlbasin SOR= Type of Aerator Aerator SAE of Aeration System 2.5 lb O;!Hp-hr 1.5 kg O:zlkW-hr Existing aerators Aeration Power Required 9.2 Hp/basin 6.8 kWlbasin One additional Section 4: Mixing system Design Design Mixing Intensity 5 Hp/MG 1.0 Wlm³ Mixing Power Required 11.3 Hp/basin 8.4 kW/basin

Blue Lake Wastewater Treatn Brewery Loading Summer Conditions Basin 1A		Prepared By SMF			
Section 1: Process Parame	ters				
AAF Design Flow Influent BOD::	0.14 MGO 308 mgll			530 m ³ tlay	
,	360 Iblday			163 kglday	
Design Effluent 900 ₅	117 mg/l 137 lb/day			62 kglday	
Influent NH-N	35 mgll 41 lb/day			19 <i>kglday</i>	
Design Effluent NH ₃ -N	32 mg/l 37 lb/day			17 kg/day	
Dooin Tomporeture (MID()	•	. E			
Basin Temperature (MID()	65 degrees	5 F		18 degrees C	
Elevation	100 ft MSL			30 m MSL	
Section 2: Basin Geometry Pond 1A					
Total Volume	0.91 MG			3,445 m	
HRT	6.51 <i>gm</i>				
Section 3:Aeration Require AOR Calculation	ments				
BOD ₅ Removed	223 lb/day			101 kg/day	
NH:rN Removed	4 lb/day			2 kg/day	
2.5 lb02/lb BODs			2.5 kg Q:zlkg BOD:		
	4.6 lb 02/lb	NH:r.N		4.6 kg O:z/kg NHN	
Total AOR to system	576 lb O ₂ /da	ay		262 kg O ₂ /day	
SOR Calculation					
SOR=	(AOR) • (C,) (a) •(p• C, · Cw} •(1.024)	III 0			
Where					
a -	0.80 -	c.=	9.78		
{\$ -	0.95 ₋ 1.07	Cw = $C112D =$	25 9.17		
() –	1.00	Temp =	16		
Therefore:					
SOR =	1,070 lb 02'da	•		486 kg 0 ₂ /day	
SOR =	45 lb 02'hi	r/basn		20 kg 02'hr/basin	
Type of Aerator	Aerator				
SAE of Aeration System	2.5 lb 02/H	p-hr		1.5 kg O ₂ /kW-hr	
Aeration Power Required				13.3 kW/basin	
Section 4: Mixing System	One additional Design				
Design Mixing Intensity	5 HpIMG	a		1.0 Wlm ³	
=9	•				

WITH BREWERY WINTER

Blue Lake Wastewater Treatment Facility Brewery Loading Winter Conditions Basin 4 Section 1: Process Parameters

Mixing Power Required

13.3 Hp/basin

Prepared By SMF 6/1112013

9.9 kW/basin

Section 1: Process Parame	eters						
Peak Day Flow Innuent 800 ₅	11	days @M mg/l	IMWWF				
Design Effluent BOD	38 lb/day 6 mg/l			17 kg/day			
Influent NH:rN	21 lbfday 9 mgfl			10 kg/day			
Design Effluent NH,-N	30 lb/day 8 mgfl				14 kg/day		
	26	lbfday			12 kg/day		
Ba,sln Temperature (Max)	65	degrees	F		18 degrees C		
Elevation	100	ft MSL			30 mMSL		
Section 2: Basin Geometry Pond 2	′						
Total Volume	2.66	MG			10,069 m ³		
	6,65	days @M	IMWWF				
AOR Calculation							
BOD ₅ Removed	17	lb/day			B kg/day		
NH ₃ -N Removed	4 lb/day				2 kg/day		
		lb Oi/lb B			2.5 kg OiJkg BODs 4.6 kg Otkg NH3-N		
Total AOR losystem	61	lbOiJday	,		28 kg O,/day		
SOR Calculation							
SOR	(AOR) • (a)'{fJ 'C Cw		,,,,,				
Where:							
(1	0 80		$C_{im} =$	9.37			
	0.95		C,,=	2.0			
()	1.03		c,2C = Temp =	9_09 18			
	1100						
Therefore:	106	Ih Orafdor	,		46 kg 0 idov		
SOR = SOR =	106 lb O:zfday 4 lb O:z(hr/basin				46 kg 0-jday 2 kg 0;ilhr/basin		
		,			3 - 7		
Type of Aerator		Aerator					
SAE of Aeration System	2.5 lb O;,!Hp-hr Existing aerators			1.5 kg O:i/kW-hr			
Aeration Power Required				1.3 kW/basin			
Section 4: MlxIng System							
Design Mixing Intensity	5	Hp/MG			1.0 W/m ³		

Blue Lake Wastewater Treatment Facility Prepared By SMF Brewery Loading Winter Conditions 11/1612013 Basin 3 Section 1: Process Parameters Peak Day Flow Influent 800₅ 0.4 MGD HI mg/l 63 lb/day 29 kgfday Des gn Efflue-nt 800₅ 11 mg/l 38 lb/day 17 kgtday 9 mgn InfluentNH3-N 31 lb/day 14 kg/day Desfgn Effluent NHrN 9 mg/l 30 lb/day 14 kg/day Basin Temperature (Max) 54 degrees F 12 degrees C Elevation 100 ft MSL $30~\mathrm{m\,MSL}$ Section 2: Basin G.eometry Pond 2 Total Volume 1.28 MG 4,845 m³ 3.20 days @MMWWF **AOR** Calculation **BODs** Removed 25 Ibfday 12 kgtday NH:rN Removed 1 lbfday 1 kg/day 2.5 lb O:i/lb BOD5 2.5 kg 02'kg 8005 4.6 lb O:z/lb NH₃-N 4:6 kg Oi}kg NH₃-N Total AOR to system 32 kg 02'day 70 lb O2/day SOR Calculation SOR = {AOR) • {C,,,,) {(.t.) "{P • C.- Cw! '(1024; '²⁰ Where: 0.80 . c.=10.71 0.95 . Cw =2.0 1.18 Csia = 9.09 0 1.00 Temp = 12 Therefore: SOR = 117 lb 02'day 53 kg 02tday SOR = 5 ib 0₂/hr/basin $2 \text{ kg } 0_2 \text{thr/basin}$ Aerator Type of Aerator $1.5~\mathrm{kg}$ 02'kW-hr SAE of Aeration System 2.5 lb 02'Hp-hr Existing aerators 1.5 kW/basin Aeration Power Required 1.g Hp/basin One additional Section 4: Mixing System Design Design Mixing Intensity 5 Hp/MG 1.0 WIm^3 4.8 kW/basin Mixing Power Required 6.4 Hp/basin

Brewery Loading Winter Conditions Basin 2	ment Facility			Prep	pared By SMF	11/6/2013
Section 1: Process Parame	eters					
Peak Day Flow Influent BODs	31	MGO mg/l			47.1. (1	
Design Effluent BODs		lb/day mgll			47 kg/day	
Infiuen! NH ₃ -N		lb/day mg/l			29 kg/day	
Design Effluent NH ₃ -N	33	lb/day			15 kg/day	
Design Emdent Ni 13-1V		mgll lb/day			14 kg/day	
Basin Temperature (Max)		degrees F			12 degree	
Elevation	100	ft MSL			30 m MS	L
Section 2: Basin Geometry	y					
Pond 2 Total Volume	1.35	MG			5,110 m ³	
	3.38	days @MI	MWWF			
AOR Calculation						
BOD ₅ Removed	41	lb/day			18 kg/day	,
NH ₃ -N Removed	2	lb/day			1 kg/day	
		lb 02/lb 80 lb 02/lb NF			2.5 kg 0 ₂ /l 4.6 kg Oa/	-
Total AOR to system	111	lb 02'day			50 kg Oz/	day
SOR Calculation						
SOR =	(AOR) •/ l'a}'{ (J•C-C,,		o			
Where:						
II' -	0.80		C _=	10.71		
(i - T -	0.95 1-18		Cw = c :10 =	2.0		
11	1.00		Temp =	9 09 12		
Therefore						
Therefore: SOR =	187	$^{\prime}$ Ib 0_2 /day			85 kg Ozf	day
SOR =	8 lb Oz/hr/basin				4 kg OiJ	
Type of Aerator		Aerator				
SAE of Aeration System		lb O₂/Hp-l	hr		1.5 kg Oi/	kW-hr
Aeration Power Required	EXisting aerators 3.1 Hp/basin One additional				2.3 kW/ba	ısin
Section 4: Mixing System						
Des gn Mixing Intensity	5	Hp/MG			$1.0~\mathrm{Wlm}^3$	
Mixing P0wer Required	6.8	Hplbasin			5.0 kWlba	sm

Brewery Loading Winter Conditions

Basin 19 Section 1: Process Parameters 1,514 m3/day Peak Dally Flow 0.4 MGD Innuent BOD₅ 65 mg/l 216 IO/day 98 kg/day Design Effluent BOD\$ 31 mg/t 104 lb/day 47 kg/day Influent NH3-N n mg/l 35 IO/day 16 kg/day Design Effluent NH₃-N 10 mg/l 33 lb/day 15 kg/day Bash Temperature (Max) 54 degrees F 12 degrees C 100 ft MSL Elevalion 30 m MSL Section 2: Basin Geometry Pond 1B Total Volume 2-25 MG 8,517 ma 5.63 days @MMWWF AOR Calculation B00₅ Removed 112 lb/day 51 kg/day NH₃-N Removed 2 lb/day 1 kg/day 2.5 kg Oi/kg BOD, 25 lb 02'1b BOD 4.6 kg O;w'kg NH3·N 4.6 lb O;iilb NH₃-N Total AOR to system 289 lb 0-jday 132 kg O:;lday SOR Calculation SOR = (AOR} " (C,,,) (a)'{P" C,.C,.) • (1 024) Where: 0.80 • C.= 10.71 (J 0.95 _ Cw = 20 c|20 =1.18 9.09 (1 1.00 Temp = Therefore: 487 lb 02'day 221 kg Di/day SOR = SOR = 20 lb O;ilhrlbasin 9 kg O:i/hr/basln Type of Aerator Aerator SAE of Aeration System 3.0 lb O:;/Hp-hr 1.8 kg O:i/kW-hr Existing aerators Aeration Power Required 6.8 Hp/basin b kW/basin One additionaJ Section 4: Mixing System Design 1.0 W/m^3 Design Mixing Intensity 5 Hp/MG Mixing Power Required 11.3 Hp/basin 8.4 kWlbash

Pfepared By SMF

1/612013

Blue Lake Wastewater Treatment Facilty

Brewery Loading Prepared By SMF Winter Conditions 1116/2013 Basin1A Section 1: Process Parameters Peak Day Flow Influent BOD₅ 0.4 MGD 108 mg/l 360 lb/day 164 kg/day Design Effluent BOD₅ 65 mg/l 216 lb/day 98 kg/day Influent NHrN 11 mg/l 37 lb/day 17 kg/day Design Effluent NHrN 11 mg/l 35 lb/day 16 kg/day Basin Temperature (Max) 54 degrees F 12 degrees C 100 ft MSL Elevation 30 m MSL Section 2: Basin Geometry Pond 1A Total Volume 0.91 MG 3.445 m^3 2.28 days @MMWWF **AOR Calculation** BOD₅ Rerpoved 144 lb/day 65 kg/day NH₃-N Removed 1 lb/day 1 kg/day 2.5 kg 0-jkg BOD₅ 2.5 lb 02/lb BODs 4.6 kg 0-jkg NHrN 4.6 lb Oi/lb NH₃ N 166 kg O₂/day Total AOR to system 366 lb 0-jday SOR Calculation SOR = (AORJ "(Cao) (t:t)"{ P " C,- C..) ·11 024) '"° Where: ti 0.B0 • C ..= 10.71 0.95 • C,,= 2.0 1.17 Ciao = 9.17 n 1.00 Temp = 12 Therefore: SOR = 620 lb O'l}day 282 kg *0-jday* 12 kg O:i/hr basin SOR = 26 lb O'J}hr basin Type of Aerator Aerator 2.5 lb 0₂/Hp-hr 1.5 kg 0₂/kW·hr SAE of Aeration System Existing aerators Aeration Power Required 10.3 Hp/basin 7.7 kW/basin One additional Section 4: Mixing System Design 1.0 Wim³ Design Mhdng Intensity 5 Hp/MG Mixing Power Required 4:6 Hp/basn 3.4 kW/basin





RIchord Somple Engineering

1197 Mugnoliu Ave Redding, CA 96001 (530) 242-1134 Fox (530) 242-1136 emoil rse@lntegrlty.com

DATE: OCTOBER 15, 2013

TO: STEVE DONOVAN, P.E, SHN CONSULTING ENGINEERS

FROM: RICHARD A. SAMPLE, P.E.

PROJECT: BLUE LAKE WWTP-MRB EXPANSION STUDY

SUBJECT: ELECTRICAL REVIEW AND RESPONSE

On Friday, September 20, I performed a site visit and documented the existing plant electrical. was able to open all equipment, with the exception of the plant service disconnect switch, photograph and take notes regarding ratings *I* loads and record actual voltage readings using a multi-meter probe as necessary for my work.

As requested, I have evaluated the existing overall plant power system to determine it's ability to support additional aeration mixer equipment.

My response is as follows:

- 1. The existing plant power service is limited to 100A at 230V, 3-phase by the service disconnect switch. The conductors, with illegible rating labeling, appear to be sized for 100A also. The conduit coming from the utility pole is 2 inch diameter, large enough for a 200A service but the conductors appear (visually from the ground) to be sized for 100A.
- 2. The pole-mounted utility service transformers are an Open-Delta configuration made up of (1) 15KVA (labeled) single phase transformer and (1) 25KVA (assumed based on size as is unlabeled). These two transformers combined create a three phase secondary service derived from a single phase primary overhead utility distribution system. The transformer combined rating of 45KVA is undersized for the calculated plant load of 51KVA, but it is not uncommon for utility companies to serve loads above the transformers rating.
- 3. The addition of either (2) 5 HP aeration mixers or (1) 7-1/2 HP aeration mixer will create an overall plant loading which exceeds the capacity and rating of the plant service.
- 4. The existing plant service panel is rated 200A, and as such would not require replacement.
- 5. The attached load calculation show loading of the plant based on a combination of existing loads and (2) new 5HP aeration mixers.
- 6. The attached overall plant power One-Line Diagram shows the plant as it would be configured with the additional mixers. Associated notes giving additional information and a description of work to be performed are listed on a separate attachment.
- 7. The attached cost estimate shows a breakdown of construction costs for reference purposes.

Attachments: Load Calculations One-Line Diagram One-Line Diagram Notes Construction Cost Estimate

SERVICE LOAD CALCULATION

Richard Sample Engineering

PROJECT: WWTP - MRB EXPANSION STUDY DATE: 10/15/13
OWNER: CITY OF BLUE LAKE JOB NO: 1306

BY: RICHARD A. SAMPLE, P.E. ENGINEERING REPORT PHASE

EQUIP. NO.	DESCRIPTION OF LOAD	NOTE	LOAD	CON.	. DEM. FACT		DEM. LOAD	
		NO.	ΗP	LOAD	UTIL	GEN	UTIL	GEN
HEADW	DRKS AREA LOADS_							
	Channel Grinder, 240V, 3-phase, Muffin Monster Cont Panel							
	In-Channel Auger, 240V, 3-phase, Muffin Monster Cont Pnl	3,5	2	2.8	0.2		0.6	
AERATIC	N BASINS							
	Mixer No.1 (Close position in basin) 240V, 3-phase Mixer No.2 (Middle position in basin) 240V, 3-phase Mixer No.3 (Farthest position in basin) 240V, 3-phase	3 3	5 5 5	6.3 6.3 6.3	1 1 1		6.3 6.3	_
	Future Mixer No. 4 (beyond baffle) 240V, 3-phase	1,3	5	6.3	1		6.3	
	Future Mixer No. 5 (beyond baffle) 240V, 3-phase	1,3	5	6.3	1		6.3	
CHLORI	NATION BUILDING	<u> </u>						-
	Chlortec System, 240V, 1-phase Inverter load	4		5.2	1		5.2	
	Duilding lighting	6.7		0.5	1.25		0.0	
	Building lighting	6,7					0.6	
	Building receptacles Miscellaneous loads	6		2.0	0.5		1.0	
	Pond #4 Recirculation pump	4	2	2.0	0.5		0.6	-
	Dosing pump, 240V, 1-phase, VFD controller	4	0.5	0.6	0.2		0.6	
OPERAT	ION BUILDING		<u> </u>					
	Service Panel 120/240V, 3-ehase, 100A, 30 gales							
	Operations Building lighting	6,7		0.3	1.25		0.4	
	Area pole lighting. (3) polelights @ 300W each	6,7		0.9	1.25		1.1	
	Building receptacles	6		2.0	0.5		1.0	
	Miscellaneous loads	6		3.0	0.5		1.5	
			_					
	-	1						
					ļ			

LOAD CALCULATION SUMMARY


CONNECTED LOAD - with future loads (shown	KVA	AMPS
shaded) UTILITY SERVICE TOTAL AT 480V, 3-PHASE	59.9	139.0
DEMAND LOAD - with future loads (shown shaded)	KVA	AMPS
UTILITY SERVICE TOTAL AT 480V, 3-PHASE	50.9	118.0

MINIMUM SERVICE DESIGN RATING: 1.25 x 118A = 148A

COMMENTS NOTES:

- 1 Equipment proposed by SHN Engineers included for system capacity sizing
- 2 Future equipment included for system capacity sizing
- 3 Equipment operates continuously, manually operated
- 4 Equipment operates intermrttently on automatic controls.
- 5 Equipment operated from packaged control panel.
- 6 Estimated bads based on panel schedules and field observations
- 7 Load factor based on National Electric Code loading requirements

,_____,shaded data indicates equipment to be added



Blue Lake WWTP One-line Diagram Notes

Note 1

Existing pole-mounted utility transformers are configured in an "Open-Delta" arrangement in order to provide three phase secondary power from a single phase primary distribution system. The utility company may choose to upgrade the transformers to serve the expanded plant loading, but it is likely that the transformers will remain as existing.

Note 2

Access to conductors at termination within the service disconnect was not possible during site visit without shutting down all power to the plant. Conduit was measured as 2 inch on building exterior which is adequate for carrying conductors rated for expanded plant loads. Existing conductors may need to be replaced with new 4/0 conductors if found to be undersized for service rated 200 ampere. Construction cost estimate is based on replacement of existing conductors with new.

Note 3

Existing service disconnect switch rated 100 ampere, 600 volts, is to be replaced with a heavy duty, service rated, fused disconnect switch rated 200 ampere, 240 volts, three phase.

Note 4

New bolt-on breaker to be provided in existing panel 3-pole space position.

Note 5

New feeder of approximate length of 250 feet is to be routed underground from the main building to new equipment rack location. Feeder is to be (3)#6, (1)#10G routed in Schedule 80 PVC conduit. Conduit is to be buried at 18 inches below grade in existing roadway. Existing asphalt will be cut, removed and replaced with new.

Note 6

New equipment rack located at corner of roadway, approximately 50 feet farther from Operations Building than Mixer #3 post mounted breaker panel.

Note 7

NEMA 4X rated wireway to be provided.

Note 8

Combination motor starter in NEMA 3R enclosure, including fused disconnect switch, NEMA starter, ON-OFF selector switch, run & fail indicating lights.

Note 9

New jacketed cable furnished by mixer manufacturer.

ELECTRICAL CONSTRUCTION COST ESTIMATE BACKUP Richard Sample Engineering

PROJECT: BLUE LAKE WWTP - MRB EXPANSION STUDY

DATE: 10/15/13

ESTIMATE BY: RICHARD A. SAMPLE, P.E.

JOB NO: 1307

RSMeans 2013 city cost index multiplier city: Eureka, California

	QUANTITY MATERIAL LABOR TO							
NO	DESCRIPTION			MATERIAL PER UNIT TOTAL		LABOR PER UNIT TOTAL		TOTAL
1	DEMOLITION	11121120112		1210 01111	101111	12100111	1011111	
а	Service breaker removal	1	JOB	50.00	50	240.00	240	290
а	Wire: THHN, copper - No. 4/0	300	LF	4.95	1,485	1.91	573	2,058
b	200A heavy duty service disc switch	1	EA	1,400.00	1,400	280.00	280	1,680
С	panel terminations	1	JOB	0.00	0	120.00	120	120
3	MIXER ELECTRICAL							
а	Trench and backfill 18"D, 18"W	250	LF	3.00	750	3.00	750	1,500
b	Asphalt replacement	250	LF	5.00	1,250	4.00	1,000	2,250
С	Conduit: Schedule 80 PVC - 1-1/2"	250	LF	4.15	1,038	4.66	1,165	2,203
d	Wire: THHN, copper - No. 6	800	LF	0.63	504	0.65	520	1,024
е	Wire: THHN, copper - No. 10	270	LF	0.24	65	0.42	113	178
f	3/4 x 48"x 48" UHMW backboard	1	EA	200.00	200	120.00	120	320
g	3" GRC posts with cap	2	EA	25.00	50	60.00	120	170
h	18"D x 30"H concrete post base	2	EA	20.00	40	60.00	120	160
i	Stainless steel channel & hardware	1	JOB	50.00	50	120.00	120	170
j	4"x4"x36" Stainless steel wireway	1	EA	200.00	200	60.00	60	260
k	NEMA 4X Combination controller	2	EA	2,300.00	4,600	240.00	480	5,080
I	50A, 3-pole feeder breaker	1	EA	60.00	60	120.00	120	180
_						_		
_	MISCELLANEOUS CONTRACTOR							000
a	Electrical permit application	1	JOB				300	300
b	Coordination with power utility Co.	1	JOB				240	240
d	Product submittals Startup and testing	1 1	JOB JOB				360 480	360 480
u u	Drawing Asbuilts	1	0 <u>00</u>				240	240
	2.a.mg/todanto		•				240	270
	SUBTOTAL				11,691		7,281	18,973
	RS Means city multiplier: Eureka				1 11,091		1.14	10,913
	SUBTOTAL				11691		8301	19992
	CONTINGENCY (@ 15%				1754		1245	2999
	OVERHEAD @ 16%						1527	1527
	PROFIT (@ 10%		1		1344		955	2299
	ELECTRICAL SUBCONTRACTOR	TOTAL						\$26,817

Item 5

To:

Mayor and Councilmembers

From:

John Berchtold, City Manager

Date:

November 13, 2013

Subject:


Authorization to Request CDBG Program Waiver for ADA

Improvements (Park facilities)

Please find enclosed the application to request a CDBG Program Income Waiver that will be submitted to the State Housing and Development Division. Funds are actually on hand at the City. The waiver, once approved, will allow funds to be utilized for ADA improvements. If unapproved, funds would be utilized for housing rehabilitation.

City Council for a number of years has directed staff to locate funding for Park facilities. This is a unique opportunity.

I recommend your authorization to submit the waiver request.



DEPARTMENT OF HOUSING AND COMMUNITY DEVELOPMENT DIVISION OF FINANCIAL ASSISTANCE

Community Development Block Grant (CDBG) Program

1800 Third Street, Suite 390 P. O. Box 952054 Sacramento, CA 94252-2054 (916) 552-9398 FAX (916) 319-8488



CDBG PROGRAM INCOME-FUNDED WAIVER REQUEST - <u>PROJECT</u> -						
JURISDICTION: City of Blue Lake	CONTACT PERSON: John Berchtold	PHONE: 7076685655 EMAIL: citymanager@bluelake.ca.go				
DATE SUBMITTED BY JURISDICTION: 11/19/13	CDBG REPRESENTATIVE: Max	Emami				
1. INDICATE CDBG ACTIVITY and MATRIX COL	DE TO BE FUNDED WITH THIS PI	ROGRAM INCOME WAIVER:				
Activity: Matrix Code:	☐ CD PROJECT	ED PROJECT				
2. INDICATE PROJECT FUNDING SOURCES:						
A. TOTAL PROJECT COST: \$100,000.00						
B. TOTAL CDBG PI WAIVER FUNDS REQUE	ESTED: \$100,000.00					
C. TOTAL NON-CDBG FUNDING COMMITTED: \$0.00 Sources of Other Committed Funding: (Indicate each funding source.) (i) 0 (ii) 0						
D. TOTAL OTHER FUNDING NEEDED: \$ <u>0</u> Funds needed but not committed: (Not i (i) Add description: n/a	Funds needed but not committed: (Not included in A. or C. above.)					
	Business Assistance: \$					
3. ACTIVITY DESCRIPTION: (Be sure to fully an	swer A. and B. below.)					
A. INDICATE ADDRESS OF PROJECT: 312 Blue Lake, CA 95525	S. Railroad					
B. REASON CDBG PI WAIVER IS BEING RE There is an urgent need to remove architect round facility so that individuals with disabili concession stand, music venue, child care fa restrooms	ural features so that accomodation ties can access the community recr	reation center,ball field,				
CPROPOSED PROJECT: (Aggregated Sco At appropriate ADA grades:construct sidewand drainage and ramping appropriate to souther	alk extensions, paving,to accomidate	e access to all facilities above,				

DEPARTMENT OF HOUSING AND COMMUNITY DEVELOPMENT DIVISION OF FINANCIAL ASSISTANCE

Community Development Block Grant (CDBG) Program

1800 Third Street, Suite 390 P. O. Box 952054 Sacramento, CA 94252-2054 (916) 552-9398 FAX (916) 319-8488



D. SCOPE OF WORK FOR CDBG FUNDING:

At appropriate ADA grades:construct sidewalk extensions, paving,to accomidate access to all facilities above, drainage and ramping appropriate to southern exterior restrooms

E. TIMELINE OF PROPOSED PROJECT: 2014-2015

5 cout.

CDBG PROGRAM INCOME-FUNDED WAIVER REQUEST - PROJECT -

JURISDICTION:				
4. ELIGIBILITY:				
A. NATIONAL OBJECTIVE:	1) \(\sum \) Low/Moderate Income Benefit (Low/Mod) 2) \(\sum \) Elimination of Slums & Blight: \(\sum \) Area Basis \(\sum \) Spot Basis 3) \(\sum \) Urgent Need			
 B. HUD LOW/MOD BENEFIT: National Objective must be met by either: 1) Beneficiaries being income restricted; 2) Beneficiaries being members of a Limited Clientele; or, 3) Service area being primarily Low/Mod individuals (>51%). Check the box that describes how this Public Service Program will meet the National Objective, and describe the details requested. 	□ Income Restricted (100 percent HUD Low/Mod Income) ☑ Limited Clientele: (Public Facility Only) List Type(s) of Limited Clientele: Seniors and severely handicapped □ Primarily Low/Mod: List % of total: □ Based on HUD Low/Mod Charts □ Based on Income Survey □ Jurisdiction-Wide □ Service Area Explain Benefit in Activity:			
C. NUMBER OF BENEFICIARIES:	81% and Above: (Non HUD Low/Mod Income (Not eligible) 597 persons (54.6%)	80% and Below: (HUD Low/Mod Income) 496 persons (45.4%)	50% and Below: (HUD Very Low/Mod Income) 298 persons (27.3%)	TOTAL: 194 disabled persons
D. DESCRIPTION OF SERVICE AREA: Submit Map(s) and Identify: (1) Census Tract/ Block Group; and, (2) Zoning in description Note: Service area information is needed regardless of which Low/Mod benefit is being used.	☐ Entire Jurisdiction ☐ Service Area(s): Describe Service Area of Project: City of Blue Lake park grounds Map Included: ☐ Yes ☐ No			
, -				

CDBG PROGRAM INCOME-FUNDED WAIVER REQUEST - PROJECT -

- INCOLCT -							
JURISDICTION:							
5. PLEASE DESCRIBE THE STATUS OF THE FOLLOWING SPECIAL CONDITIONS:							
DAVIS BACON COMPLIANCE:	 □ Davis Bacon and Related Acts is triggered by this project (including Prevailing Wage): □ Labor Standards Compliance Officer will be in-house Jurisdiction staff member □ Labor Standards Compliance Officer will be procured under Federal guidelines □ Davis Bacon and Related Acts is NOT triggered by this project (include explanation and supporting documentation) 						
ENVIRONMENTAL AND NEPA COMPLIANCE:	Jurisdiction has completed the Environmental Finding Form and the Level of Determination indicates the NEPA review will be: Exempt Categorically Excluded, Subject to 58.6 Categorically Excluded, NOT Subject to 58.6: Statutory Worksheet Environmental Assessment Environmental Reviewer and Certifying Officer will be members of Jurisdiction staff Environmental Review Consultant will be procured under Federal guidelines. And, Certifying Officer will be in-house member of Jurisdictional staff						
CITIZEN PARTICIPATION:	Indicate the status of each of the following: Public Notice: ☐ Completed ☐ Not Completed Comments: Resolution of the Governing Body (Authorizing submittal of PI Waiver Request, designating the Authorized Representative and approving transfer of funds): ☐ Completed ☐ Not Completed Comments:						
6. COMPLIANCE OF	SPECIAL CONDITIONS UPON APPROVAL:						
RELOCATION COMPLIANCE:	 □ If this project triggers Relocation, the Jurisdiction will comply with the Uniform Relocation Act, Section 104(d) before a release of CDBG PI funds occurs. □ If this project triggers Relocation, the Jurisdiction will submit a specific Assistance Relocation Plan for this activity prior to releasing CDBG PI funds. □ This project will not involve Relocation and, therefore, the Jurisdiction will submit a letter explaining why no displacement or relocation will occur. 						
SITE CONTROL:	 ☑ Upon approval, the Jurisdiction will demonstrate site control of the proposed property by submitting evidence to the Department. ☐ Other – Describe: 						
FUNDING COMMITMENTS:	☐ The Jurisdiction will demonstrate that all funding required for project completion must be documented and committed before a release of CDBG PI funds occurs. (Must verify information in Section 2 C. above.)						
PI WAIVER ADMINISTRATION:	The Jurisdiction understands that, upon approval of this CDBG PI Waiver, it will provide documentation which indicates the activity administrator for the CDBG PI Waiver activity. If procured, the Jurisdiction will provide documentation of the procurement method used (per 24 CFR 85.36).						
PROGRAM INCOME REUSE PLAN:	☐ The Jurisdiction understands that, upon approval of this CDBG PI Waiver, a copy of a new or revised Program Income Reuse plan to include the CDBG PI funded project must be submitted to the Department for approval before a release of CDBG PI funds occurs.						
SECTION 504 ACCESSIBILITY REQUIREMENTS:	The Jurisdiction understands that Section 504 Regulations apply when CDBG funds are used on a public facility project or when an existing Public Facility or Housing Project with fifteen (15) or more units is being purchased and/or "substantially" rehabilitated. Qualified CDBG-assisted Housing Projects are required to have a certain percentage of						
OTHER:	the units designed for and accessible to persons with mobility and sensory impairments.						

5 cont.

CDBG PROGRAM INCOME-FUNDED WAIVER REQUEST - PROJECT -

	- FROJECT -
On behalf of the City/County of: Blue Request and understand that, upon a met and all federal overlay requirements	Lake I submit this CDBG Program Income Waiver pproval, all applicable Special Conditions must be a must be complied with.
Authorized Representative Signature:	
Date: 11/19/13	
Print Name and Title of Authorized Signer:	
John D. Berchtold	
<u> </u>	
Print Name of Preparer: John D. Berchtold	Date: <u>11/19/13</u>
This project has been identified in the City's Strateg	nall community of 1,248. It has very limited General Fund funding. gic Plan as being a critical need. We are fortunate that the State
other residents of Humboldt County, most of whom	residents and visitors with disabilities. This facility is also utilized by come from a 15 mile radius. Our estimate of \$100,000.00 comes
to you after meeting with our City Engineer, Public	Works Staff,and Park Staff.
(EOD HOE	
	BY CDBG PROGRAM ONLY)
JURISDICTION:	
7. PROJECT APPROVAL:	
☐ APPROVED	☐ CONDITIONALLY APPROVED
Activity Eligibility 105(a):	
☐ NOT APPROVED Date:	
8. CONDITIONS FOR APPROVAL <u>OR</u> REASON	S FOR NOT APPROVING:
A STATE OF THE STA	
DBG Representative:	Date:

7	(ONT	•

CDBG Program Manager:	Date:
CDBG Section Chief:	Approved Date:




CITY OF BLUE LAKE

Post Office Box 458, Phone 707.668.5655

111 Greenwood Road,

Blue Lake, CA 95525 Fax 707.668.5916

Attached is the 2010 Census Block Map for Blue Lake. The "Census Tract" for the City is 103 and the "Census Block" that includes Perigot Park is 3052. Also attached is a modified version (8.5" x 11") of the City's Zoning Map which shows the zoning for Perigot Park. The Park is zoned Open Space/Recreation or "X" zone. Let me know if you need any additional information.



To: Mayor and Councilmembers

From: John Berchtold, City Manger

Date: November 13, 2013

Subject: Presentation by Michael Fields, Dell Arte

Michael intends to make a presentation regarding the recent Harvest Festival, future activities and some thoughts regarding Humboldt Made.

No action is requested.

To:

Mayor and Councilmembers

From:

John Berchtold, City Manager

Date:

November 14, 2013

Subject:

Award for "Wastewater Plant of the Year"

This award was presented by the California Water Environmental Association (North Coast Region) for the 2013 improvements made at the sewer plant (dikes and weirs). This is a major accomplishment for such a small community as Blue Lake.



California Water Environment Association

and its

NORTH COAST SECTION

present to

CITY OF BLUE LAKE



this

Plant Of The Year Award Less than 5 MGD 2013

City of Blue Lake

City Council Agenda

Item#: ____8___

Date: 19 November 2013

Subject: SHN Greenwood Road Geometric Assessment Report of Findings Re-Visited with Recommended Changes

To: City Council and Staff

From: Sherman Schapiro, Blue Lake resident

Attachment: Bring your SHN Study

Background: In July of this year, the City Council received an SHN Study with subject: Greenwood Road Geometric Assessment Report of Findings. As part of his introduction to this agenda item, the City Manager noted that:

"This study is a precursor to funding for the re-building of Hatchery and Railroad roads. In other words, this places us in a "ready" mode should federal funds become available."

I pointed out some initial concerns with this report at the July meeting and I am now able to list what I believe are 3 flaws with the report. Additionally, I list several possible low-cost improvements at the intersection that could be implemented now. I am also presenting a petition signed by over 40 Blue Lake residents, including most households/property owners who live or own property in close proximity to the project area, that shows near unanimous opposition to the recommended Option 2 design. The individuals saw the project as being unnecessary adding their concern that much of the traffic along this corridor already goes too fast and the recommended improvements will only allow for greater speeds. Furthermore, the signers are opposed to any design change that could lead to increased speeds. I would make note from the report that accidents have not been a problem at the intersection.

<u>Discussion</u>: I see 3 major problems with the SHN study that need addressing and I list also additional information, comments, and suggestions as well.

- 1. I feel the comments in the manager's report are an overstatement which goes beyond the scope of the prepared study. The study was very limited as the title states (A Geometric Assessment). It did not consider a number of factors including community and environmental impacts of the project. The study also did not look at any alternatives some of which might easily be implemented in the near future, and in a less costly manner. Yet, the report recommends options which then the manager's notes state puts the City in "ready" mode.
- I believe that for the SHN study and its conclusions to be interpreted correctly, the limits of the study need to be spelled out at the beginning. I would recommend the addition of a qualifying paragraph at the start of the study which would reflect the true status of the report. Perhaps something such as:

"This current study is limited in scope to a geometric assessment and should be considered quite preliminary. A more complete study including environmental and other impacts as well as public input would need to be completed and accepted by the City Council before any recommendations including those herein could be taken as conclusive or definitive, let alone as being indicative of a "ready mode" project."

- 2. The report has a significant omission. It gives no consideration to the physical presence of the residential structure at 110 Greenwood. If one goes out to the E Street corner, one will see that this structure seriously limits the view at the intersection regardless of modification. But this was not mentioned in the text. Furthermore, this structure was omitted from Figures 2, 8, and 9 depicting the intersection; the latter two of which show possible intersection design changes. Because of this, the drawings do not truly reflect the impact that the changes might have on the property. In fact, it appears that Option 1 in Figure 8 might very well put the roadway through much of the structure itself. When I asked about this omission at the July meeting, I was told that SHN never gathered the measurements necessary to include this structure in the drawings. I believe this is a serious flaw/omission in the report and the report is incomplete without visually showing these impacts. The current drawings make it appear that the City is dealing with an empty lot which is both incorrect and definitely misleading.
- 3. The study also omits the required stopping sight distance for a 15 mph rated turn which is the current configuration. If it is 125 ft at 20 mph as reported, could it be that the current 90 ft sight distance is sufficient for the intersection as it stands? Also, would this sight distance increase if measure 5.a) listed below were implemented?
- 4. I would make note from the petition that there is overwhelming opposition to any change allowing increased speeds from those who would be most affected by these changes. This would include opposition to the "recommended" Option 2 design,
- 5. I would recommend that the Council members and City staff go out and look at the corner at E Street. When there, consider the following possible recommendations some of which should be considered independently.
- a) Move the Stop Line outward 10' or more for better visibility. In order to proceed safely, most drivers must pull out that far anyway so the Stop Line should be moved to accommodate this. For reference, check out the position of the Stop Line at the other corner at E and First as well as the fenced corner at Hartman and Blue Lake Boulevard.
- b) E Street is a lightly trafficked road. The vast majority of traffic on E Street turns off Greenwood toward $1^{\rm st}$ Avenue. Make E Street one way towards First in the right hand lane as presently configured. Redesign the other lane into a bike-pedestrian way. This eliminates most of the visibility problems as turns off E Street would no longer be possible.
- c) With appropriate truck route signage, put in a crosswalk across Greenwood from the E Street corner to the City Hall parking lot corner for travel to and from City Hall and the Park. Many cross here now.
- d) Put in larger signage on the truck route turn showing the recommended 15 mph speed limit. The "15" on the current signage is too small. When I mentioned this to those I spoke with, most never had noticed the number 15 was there. As far as travel times go, the difference between going 100 yards at 30 vs. 15 mph is roughly 7 seconds. I doubt that actual traffic speeds are affected that much at the intersection but this shows how negligible such speed changes are on travel time.

6. For the sake of clarity for both the public and City Council, I would ask what official steps would the City need to take to apply for a grant and also implement a change such as the Option 2 design for example? What are the required environmental or community impact studies, public noticing and hearings, etc?

Possible Actions: I would recommend to the City Council that it officially find that the current report is incomplete and needs amending. Specifically, I would request that the changes noted in 1., 2., and 3. above be made. This includes taking the necessary measurements to modify the figures to show the presence of the structure at 110 Greenwood. I would also request that the City Manager make a finding that the options presented are preliminary and not what one would call "ready" as they are the findings of a very limited study. Many more steps would be needed before a "ready" design can be put forward. Upon conclusion, the amended report should be passed on to HCAOG who paid for the study.

I would also suggest that the Council direct staff to acquire the information to answer the question raised in point 6. Since Staff has already begun a process to be "ready" to look at the truck route and federal grants, I think the Council and public should have an understanding of the steps required to get a grant and get a design approved by the City Council.

I invite you to go out and examine this intersection yourself. I provide the list of recommendations in 5.a) through 5.d) for the City's consideration. I do think that items a), c), and d) would be a benefit to the residents of Blue Lake and have merit at this time.

Petition Opposing Greenwood-Railroad Intersection Changes

We the undersigned Blue Lake residents or property owners oppose any physical changes to the Greenwood Road - E Street - Railroad Avenue - Broderick Lane intersection including those being currently proposed. We believe such changes would allow for increased speed on the Greenwood - Railroad route through the intersection that would carry over throughout the entire length of the primarily residential corridor making the entire route less safe for both drivers and pedestrians. The current configuration requires reduced speed at the intersection, and as such, acts as built-in traffic-calming for the route's entire length. Designs that allow increased speeds through the intersection would have the opposite effect. Accidents at this intersection have been rare so we see no need for physical changes, but we do recommend better signage of the posted reduced speed limit along the curved path through the intersection itself to encourage safer driving.

<u>Print Name</u> <u>Signature</u> <u>Blue Lake Street Address</u>

COMPLETED COPIES WILL BE PASSED OUT AT THE COUNCIL MEETING.

FROM COUNCILMEMBER LANA MANZANITA

HWMA's purposed Legislative Goals: Background- HWMA has decided that
the Board should be in the "driver's seat" in selecting the kind of legislation,
both federal/state that they want to support this year. A sub-committee
(Lana Manzanita and Mike Newman) met with HWMA Director (Jill Duffy)
and drafted the goals using HWMA's Strategic Plan as a guide.

Purpose: City Council members review materials and clarify/discuss these goals.

Action: Council reaches consensus on HWMA'S legislative goals.

Humboldt Waste Management Authority Proposed Legislative Goals

November 2013

This list is not comprehensive and could include additional topics and goals.

Support

Recycling

- Legislation towards the procurement of recyclable and recycled-content materials
- Promotion of source reduction measures.
- Strengthen manufacturer responsibility for electronic waste recycling and support local collection programs.
- Efforts to strengthen curbside recycling programs.
- Legislation that promotes reduced packaging and Extended Product Responsibility (EPR).
- Legislation and other efforts that promote use of multi-use bags by consumers and to reduce the prevalence of single-use bags in the environment.
- Legislation and other efforts that facilitate funding, collection and proper disposal of waste pharmaceuticals.
- Funding mechanisms to support diversion programs.

Materials Market Development

- Measures that promote market development of recyclable materials
- Legislation and other efforts to increase the markets for recycled materials, including advanced disposal fees, minimum content laws, and recycling market development zones.

Conversion Technologies

- Legislation encouraging use of organics anaerobic digestion and/or solid waste conversion technologies capable of minimizing the amount of solid waste sent to landfills, and do not impede or impair existing and planned recycling and waste reduction programs.
- Financial and other incentives to assist in implementing compliance programs using green technology including, but not limited to diversion credits for new technologies designed to convert waste materials into usable energy, renewable energy credits, tax credits, and greenhouse gas reduction credits.

Miscellaneous

- Encourage the streamlining of Cal Recycle grant programs and provide maximum flexibility to local government, including JPA's
- Encourage legislation for funding collection and management of pharmaceutical waste.
- Encourage 'green chemistry' initiatives promoting use of less toxic materials for material production.

Oppose.

- Oppose legislation that would preempt local land use authority over solid waste facilities, or otherwise restrict the ability of a county or city to issue a land use permit for a solid waste facility, or restrict the ability of a county or city to apply conditions to such facilities through the conditional permit process.
- Oppose legislation restricting the ability of local governments to regulate solid waste and recyclable materials.

FROM COUNCILMEMBER LANA MANZANITA


 Legislative Webinar Report: Background- This is a League report from the 2013 California legislation bills that was either supported or opposed by the League and their ramifications to cities. The report also contains the League's outlook for 2014 bills that are being considered by the Legislature.

Purpose: The Councilmembers review materials and ask questions concerning webinar.

Action: Discussion



2013 Legislative Briefing



Webinar: November 6, 2013


96

Progress on League Strategic Goals

partnerships with new and returning state policy-makers and other stakeholders #1 Goal: Develop and strengthen long-term relationships and

- new legislators. Regional divisions hosted meetings and receptions with
- in Sacramento. League leadership and lobbyists met with legislators
- partners in local government, business and other Relations strengthened with traditional

organizations.





Progress on League Strategic Goals

increased funding for essential local services. investment in public infrastructure, expansion of affordable housing, and #2 Goal: Develop and advocate for new tools and funding options for community and economic development to support job creation


Administration to engage. Many bills are pending and can be pursued As detailed earlier, this was a primary focus of the legislative efforts of in the second year of the two-year session. the organization in 2013. The key challenge is getting the





Progress on League Strategic Goals

services for city residents. reform to ensure the long-term affordability and responsiveness of public **#3 Goal:** Continue and expand upon recent efforts at pension and OPEB



- Participated and tracked administrative implementation of 2012 pension reform.
- Formed city advisory group to CalPERS.
- options on OPEB issues Internal city manager group continues to discuss





Progress on League Strategic Goals

partners and the public can expect from the League, its products and services. communicates the League's identity along with the unique benefits that city officials, our **#4 Goal:** Develop and implement a marketing and branding strategy that effectively



- Formed taskforce.
- Conducted research.



communicates its brand, with its primary audience remaining city officials. makers and the press. Suggestions primarily focus on fine-tuning ways the organization Initial conclusions: The League retains a strong brand with local officials, policy

96

Out 00 K Tor 2014



- Governor's re-election.
- Changes in legislative leadership.
- Water bond discussions.
- Lower vote thresholds.
- Time to make progress on economic development, infrastructure and affordable housing?





Housing, Community and Economic Development

Kirstin Kolpitcke, Legislative Advocate kkolpitcke@cacities.org



What to expect in 2014

- Regulation of Sober Living Homes.
- Regulation of Massage Establishments.
- More attempts to make changes to CEQA.



Administrative Services and Employee Relations

Natasha Karl, Legislative Advocate nkarl@cacities.org





Looking Ahead to 2014

Issues on the Horizon

- Cleanup Pension Reform Regulations and Possible Legislative
- improvements) impact employer rates (i.e., discount rate, mortality Additional Policy Changes at CalPERS that may
- Collective Bargaining, PERB and "genuine impasse"
- Possible Brown Act Cleanup



96

Environmental Quality and Community Services

Jason Rhine, Legislative Advocate jrhine@cacities.org



96

Mat to Watch in 2014

- Water Bond Stormwater
- Single-use Carryout Bags
- Cap and Trade Auction Revenue
- California Safe Drinking Water Act
- Mandatory Commercial Organics Recycling
- Prop 39 Funding





COBBUSITY SET ICES

AB 265 (Gatto) Local Government Liability: Dog Parks (Pg. 22)

dog park. for injury or death of a person or pet resulting solely from actions of a dog in a Clarifies that a public entity that owns or operates a dog park will not be liable

AB 465 (Bonilla) Youth Sports: Criminal Background Checks (Pg. 20)

coach or hired coach candidate. background checks, as well as subsequent arrest notification(s), for a volunteer Clarifies that community youth athletic programs may request state and federal



What to Watch in 2014

- Improving Economy Pressure to Fund Community **Programs**
- California Arts Council



Public Safety

Tim Cromartie, Legislative Advocate tcromartie@cacities.org



What to Watch in 2014

- Medical Marijuana
- Gun Control
- Corrections Prison Population Management
- Identity Theft
- Wireless Cameras



961



Connuncation, and

Tansportation,

Jennifer Whiting, Legislative Advocate jwhiting@cacities.org



What to Watch in 2014

- Transportation Funding
- Overweight Buses
- Online Transportation Companies
- Disabled Parking Placards
- Electric Vehicles
- Broadband Roll-Out
- UUT Collection for Prepaid Wireless Services
- MAP-21 Reauthorization







Revenue and Taxation

Dan Carrigg, Legislative Director dcarrigg@cacities.org



96,

Kevenue and laxation

Looking Ahead

- Fixing annexation/incorporation funding (SB 56)
- Lower vote thresholds.
- Use tax collection: Federal Marketplace Fairness Act.
- Prop 218 storm water clean up.
- Extension of dates on Controller's financial reporting forms.
- Moving forward on economic development.





From Council Member Manzanita:

Develop a concrete "check off list" of tasks for Strategic Plan Goal of
 Expand Business in the Industrial/Business Park. Background- The Council
 has invested many meetings to this subject without a clear vision of what
 comes next and what elements should or should not be in our plan.

Purpose: Discuss this in some depth so that we can direct staff to help us develop a roadmap for this goal. There are no materials to review, but the pages under title Economic Development-Strategic Plan, seems to be a good place to start.

Action: Discussion followed by direction to staff.

To: Mayor and Councilmembers

From: John Berchtold, City Manager

Date: November 14, 2013

Subject: Grant Opportunity – Resurfacing of Railroad Avenue between E and

G Streets

Mike Foget, City Engineer has been advocating for funding for resurfacing of Railroad Avenue. HCAOG has funding available for rehabilitation (re-surfacing). This is very rare and the governmental units in the County compete for these funds. As of this writing (Thursday), the Technical Advisory Committee of HCAOG is meeting to recommend project funding. If so recommended, I will bring this matter forward to City Council on Tuesday night. The next step is drafting of a Project Service Report (PSR) by the City Engineer for these two (2) blocks.

For clarification purposes, this project requires no re-alignment. Further, it is not in the area of concern cited by Mr. Schapiro.



City of Blue Lake

Check/Voucher Register - City Council Check Report From 10/1/2013 Through 10/31/2013

Check Number Check Date Payee			Check Description	Check Amount	
36190	10/4/2013	Amanda E. Arthington	Employee: arthingtona; Pay Date: 10/4/2013	27.40	
36191	10/4/2013	John D. Berchtold	Employee: berchtoldj; Pay Date: 10/4/2013	2,314.03	
36192	10/4/2013	Glenn R. Bernald	Employee: bernaldg; Pay Date: 10/4/2013	1,348.82	
36193	10/4/2013	Harold D. Burris	Employee: burrish; Pay Date: 10/4/2013	1,227.18	
36194	10/4/2013	Courtney D. Dexter	Employee: dexterc; Pay Date: 10/4/2013	313.09	
36195	10/4/2013	Michael A. Gibson	Employee: gibsonm; Pay Date: 10/4/2013	233.63	
36196	10/4/2013	Vivian S. Harp	Employee: harpv; Pay Date: 10/4/2013	191.83	
36197	10/4/2013	Vicki L. Hutton	Employee: huttony; Pay Date: 10/4/2013		
36198	10/4/2013	Jacob P. Meng	Employee: muttony, 1 ay Date: 10/4/2013 Employee: mengj; Pay Date: 10/4/2013	1,001.72	
36199	10/4/2013	Logan J. Morrow		595.05	
36200	10/4/2013	Kara A. Newman	Employee: morrowl; Pay Date: 10/4/2013	749.22	
36201	10/4/2013	Adrienne L. Nielsen	Employee: newmank; Pay Date: 10/4/2013	1,092.57	
36202	10/4/2013		Employee: nielsena; Pay Date: 10/4/2013	1,012.96	
36202		Loren M. Thompson	Employee: thompsonl; Pay Date: 10/4/2013	104.14	
36203 36204	10/4/2013	Melissa M. Toledo	Employee: toledom; Pay Date: 10/4/2013	396.82	
	10/4/2013	Robert Wojciechowski	Employee: wojciechowskir; Pay Date: 10/4/2013	36.54	
36205	10/4/2013	Kernen Construction	9/30/13 inv no 48351 Dike Repair	215,583.98	
36206	10/4/2013	Wendy Howard	Sep 2013 accounting services	396.06	
36207	10/4/2013	John Roberts	Sep 2013 statement	710.00	
36208	10/4/2013	Sudden Link	2-Oct 2013 statements	203.90	
36209	10/4/2013	T. I. Smith Electric	9/18/13 inv no 1665-2013	255.00	
36210	10/4/2013	Advanced Security Systems	9/23/13 statement	162.00	
36211	10/4/2013	AT&T	2-9/20/2013 billings	63.42	
36212	10/4/2013	City of Blue Lake	10/1/13 water/sewer billings	1,731.27	
36213	10/4/2013	B & B Portable Toilet Co.	9/27/13 inv no 39R00052	76.50	
36214	10/4/2013	CA State Disbursement Unit	10/4/2013 PR deductions - CS	132.46	
36215	10/4/2013	Employment Development Dept.	UI, SDI & PIT 10/4/13 PR	631.95	
36216	10/4/2013	Cal PERS	retirement pmt 10/4/13 PR w/adj.	3,594.54	
36217	10/4/2013	D & R Janitorial Service	Sep 2013 janitorial services	295.00	
36218	10/4/2013	Eureka Boiler Works	9/30/13 statement	93.81	
36219	10/4/2013	GE capital	9/25/13 inv no 59499479	196.73	
36220	10/4/2013	Humboldt County Tax Collector	7/1/13-6/30/14 property tax		
36221	10/4/2013	Hensell Materials, Inc.	10/1/13 statement	47.90	
36222	10/4/2013	The Mill Yard	9/30/13 statement	17.97	
36223	10/4/2013	Mendes Supply Company		887.25	
36224	10/4/2013	Miller Farms Nursery, Inc.	10/1/13 statement	212.87	
36225	10/4/2013		9/30/13 statement	328.04	
36226	10/4/2013	McKinleyville Ace Hardware Redwood Coast Energy Authority	9/30/13 statement May-Jun, Jul, Aug 2013 invoices RCEA-BL-SGC-4/5/6	364.47 2,046.00	
36227	10/4/2013	Specialty Traffic Systems	10/1/13 statement	17.20	
36228	10/4/2013	Three G's Hay & Grain		17.30	
36229	10/4/2013	US Bank Corp. Payment Systems	9/30/13 statement	119.00	
36230	10/4/2013	Verizon Wireless	9/23/13 statement	1,755.26	
36231	10/4/2013		Aug 22-Sept 21, 2013 inv no 9711916248	478.75	
36232		West Coast Plumbing	10/1/13 statement	64.42	
	10/4/2013	Pacific Gas and Electric	9/18/13 #5154205317-1 & 9/24/13 #9126744508-7	7,047.77	
36233	10/16/2013	Streamline Planning Consultant	inv no's 12343, 12344 & 12357	5,173.22	
36234	10/16/2013	ACWA/JPIA	Nov 2013 health insurance	14,407.35	
36235	10/16/2013	Department of Justice	10/3/13 inv no 996998	32.00	
36236	10/16/2013	Nancy Diamond	9/1/13 inv#1498 & 10/1/13 inv#1509	3,711.00	
36237	10/16/2013	Humb. Bay Municipal Water Dist	Sep 2013 billing period	13,861.34	
36238	10/16/2013	Kernen Construction	9/27/13 inv no 48272	1,039.24	
36239	10/16/2013	LCC-Redwood Empire Division	9/19/13 inv no's 1269 & 1278	60.00	
36240	10/16/2013	U. S. Postal Service	postage stamps	276.00	
86241	10/16/2013	Arcata Scrap & Salvage	9/16/13 inv#3518 & 9/27/13 inv#3523	125.57	
66242	10/16/2013	Kevin Benjamin	Sep 2013 meetings	60.00	
66243	10/16/2013	Lana Manzanita	Sep 2013 meetings	120.00	
			-	120.00	
66244	10/16/2013	Renner	9/30/13 inv no 250308	2,036.67	

City of Blue Lake

Check/Voucher Register - City Council Check Report From 10/1/2013 Through 10/31/2013

Check Number	Check Date	Payee Check Description		Check Amount	
36245	10/16/2013	Kara A. Newman	9/6/13-9/13/13 mileage reimb.	31.6	
36246	10/16/2013	Kara Newman	Jun 2013 & Aug 2013 planning meetings	200.0	
36247	10/16/2013	North Coast Laboratories LTD.	9/30/13 statement	360.0	
36248	10/16/2013	Adrienne Nielsen - Petty Cash	reimb. BO petty cash account	63.1	
36249	10/16/2013	SWRCB Office of Operator Cert.	WWTP examination - Morrow	140.0	
36250	10/16/2013	SHN	8/16/2013 inv no's 80587 & 80590	13,992.9	
36251	10/16/2013	Arcata Stationers	10/1/13 statement	48.6	
36252	10/18/2013	Amanda E. Arthington	Employee: arthingtona; Pay Date: 10/18/2013	18.2	
36253	10/18/2013	John D. Berchtold	Employee: berchtoldj; Pay Date: 10/18/2013		
36254	10/18/2013	Glenn R. Bernald	Employee: bernaldg; Pay Date: 10/18/2013	2,314.02	
36255	10/18/2013	Harold D. Burris	Employee: bernalag, 1 ay Date: 10/18/2013	1,348.82	
36256	10/18/2013	Elizabeth A. Cardoza	Employee: cardozae; Pay Date: 10/18/2013	1,182.56	
36257	10/18/2013	Courtney D. Dexter	Employee: dexterc; Pay Date: 10/18/2013	149.81	
36258	10/18/2013	Michael A. Gibson		442.43	
36259	10/18/2013	Vivian S. Harp	Employee: gibsonm; Pay Date: 10/18/2013	259.26	
36260	10/18/2013	Vicki L. Hutton	Employee: harpy; Pay Date: 10/18/2013	96.82	
36261	10/18/2013	Jacob P. Meng	Employee: huttony; Pay Date: 10/18/2013	1,001.71	
36262	10/18/2013	Logan J. Morrow	Employee: mengj; Pay Date: 10/18/2013	595.05	
36263	10/18/2013	Kara A. Newman	Employee: morrowl; Pay Date: 10/18/2013	624.65	
36264	10/18/2013		Employee: newmank; Pay Date: 10/18/2013	1,092.56	
36265		Adrienne L. Nielsen	Employee: nielsena; Pay Date: 10/18/2013	1,012.96	
36266	10/18/2013	Loren M. Thompson	Employee: thompsonl; Pay Date: 10/18/2013	84.62	
	10/18/2013	Melissa M. Toledo	Employee: toledom; Pay Date: 10/18/2013	350.72	
36267	10/18/2013	Robert Wojciechowski	Employee: wojciechowskir; Pay Date: 10/18/2013	36.54	
36268	10/23/2013	AT&T	4-10/4/13 statements	226.91	
36269	10/23/2013	Access Humboldt	9/30/13 inv no 691	112.50	
36270	10/23/2013	Blue Lake Rancheria	Sep 2013 purchased transportation	2,625.00	
36271	10/23/2013	Blue Lake Casino	Sep 2013 fuel bill	725.00	
36272	10/23/2013	Blue Lake Casino	WWTP loan pmt due 10/1/13	2,966.94	
36273	10/23/2013	Employment Development Dept.	UI, SDI & PIT pmt 10/18/13 PR	642.44	
36274	10/23/2013	CA State Disbursement Unit	10/18/13 PR deduction - CS	132.46	
36275	10/23/2013	Cal PERS	retirement pmt 10/18/13 PR	3,549.60	
36276	10/23/2013	DocuStation	10/9/13 inv no 12176	214.66	
36277	10/23/2013	Gabriel Enriquez, DDS, MS	10/17/13 orthodontic pmt - Bernald	474.00	
36278	10/23/2013	Freedom Voice	10/1/13 inv no 116889	109.58	
36279	10/23/2013	Franklin's Service	9/30/13 statement	38.61	
36280	10/23/2013	Humboldt County Sheriff's Dept	Nov 2013 animal shelter services	543.00	
36281	10/23/2013	Humboldt County Health Dept.	3-10/1/13 bills Skate Conc/Corp Yard/WWTP	1,241.35	
36282	10/23/2013	Terminix International	9/5/13 CH & PH pest control	68.00	
36283	10/23/2013	Lawrence G. Johanson, DDS, Inc	dental pmt 10/1/13 Morrow	1,001.50	
36284	10/23/2013	Lawrence G. Johanson, DDS, Inc	dental pmt 10/16/13 Hutton	110.00	
36285	10/23/2013	Harbor Freight Tools	9/27/13 #609224, 10/10/13 #611520	37.09	
36286	10/23/2013	Intedata Systems	9/30/13 statement	420.00	
36287	10/23/2013	Kernen Construction	10/7/13 inv no 48393	3,000.00	
36288	10/23/2013	Ron and Mary Richard	Richard-loan pmt due 11/1/13	1,258.22	
36289	10/23/2013	U. S. Department of Treasury	10/18/13 PR garnishment	110.23	
66290	10/23/2013	Planwest Partners, Inc.	Sep 2013 statement	660.00	
66291	10/23/2013	Sport & Cycle Inc.	9/24/13 statement	233.09	
6292	10/23/2013	NYLEX.Net	10/17/13 inv no 74644		
66293	10/23/2013	Carli French	French 9/28/13 facility rental deposit refund	438.98 100.00	

11a cont.

CITY OF BLUE LAKE Refund Check Report

2:06:36 PM		10	10/31/2013		Page 1 of	f 1
Account #	Name	Address		Service Address	Refund	Check #
20366401	O'SHELL, KAREN			521 VANCE LAKE LN #B	105.69	
		P. O. BOX 722 BLUE L AKE, CA		Deposit Applied	: 130.00	
		DEGE EARE, OA	95525-0722	Deposit Interest	.00	
				Non-Deposit Credits	s: .00	
40528001	ROSS, BERNARD			630 J ST	25.07	
		P.O. BOX 9451 MARIETTA, GA		Deposit Applied	102.00	
		WARIETTA, GA	30065	Deposit Interest		
				Non-Deposit Credits	.00	
00000000	CITY OF BLUE LAN	KE P O Box 458			469.24	
		Blue Lake, CA				
			95525-0458			
Total number	of checks:	3	То	tal Customer Refund Checks:	130.76	
				Total Of All Deposits Applied:	600.00	
				Total Of All Deposit Interest:	.00	
		Т	otal Reimbursable	Non-Deposit Credits Included:	.00	_
			Tot	al Of Checks Drawn On Bank:	600.00	
			(Less) - To	otal Customer Refund Checks:	130.76	_
			Charges/	Credits Paid By Deposit Acct.:	469.24	

lla.cont.

CITY OF BLUE LAKE

Disbursement Report for Month: October Year: 2013

Disbursements other than Checks

Description	Date	Amount
IRS 941 Disbursements through the Electronic Federal Tax Payment System (EFTPS)	10/04/13	\$4,042.21
IRS 941 Disbursements through the Electronic Federal Tax Payment System (EFTPS)	10/18/13	\$4,057.12
IRS 941 Disbursements through the Electronic Federal Tax Payment System (EFTPS)		
IRS 941 Disbursements through the Electronic Federal Tax Payment System (EFTPS)		
	Total :	\$8,099.33

The Blue Lake City Council met in regular re-scheduled session at 7:00 p.m. on November 5, 2013. Mayor Sherman Schapiro called the meeting to order. Council Members present were Stephen Kullmann, Kevin Benjamin, Greg Sawatzky, and Lana Manzanita. Others present were City Manager John Berchtold and City Clerk Adrienne Nielsen.

Motion to Approve Agenda

Councilmember Benjamin moved, seconded by Councilmember Sawatzky to approve the agenda after moving item six after item seven. The motion carried unanimously.

Public Input

A citizen residing on K Street addressed the Council with concern of shootings at his property and neighbor's property. He stated that he has reported it to the Sheriff in years past with no resolve. City Manager Berchtold referred him back to the Eureka Sheriff Department.

Proclamation for the Great American Smokeout November 21, 2013 (Action)
Mayor Schapiro read Proclamation for the Great American Smokeout November 21,
2013. Lin Glen stated that the focus is on electric smoking devices and may come back
to Council to add e-cigarettes to the City's ordinance. Councilmember Benjamin
moved, seconded by Councilmember Sawatzky to approve the proclamation. The
motion carried unanimously.

Public Safety Commission Report on Sheriff Contract (Action)

Lin Glen, Public Safety Commission member, spoke to Council about the recommendations from the Public Safety Commission regarding the Sheriff contract. After brief discussion, Councilmember Manzanita moved, seconded by Councilmember Benjamin to approve the recommendations of the Public Safety Commission and direct the City Manager and Mayor Schapiro to commence formal negotiations for a new Sheriff contract. The motion carried unanimously.

Sewer Generator and Automatic Transfer Switch – Monda Way Lift Station (Action)

City Manager Berchtold reported to Council that the Industrial Park tenants transfer sewer through a pump and that backup for that pump is a generator that must be manned at all times. He stated a better solution is a permanent generator and that the City accepted two proposals. Councilmember Kullmann moved, seconded by Councilmember Benjamin to approve the proposal from Brant Electric for the generator replacement cost of \$13,734.00. The motion carried unanimously.

Councilmember Manzanita - Council Discussion on Purchasing Presentation Equipment for City Council Chamber (Discussion)

Council discussed purchasing presentation equipment for the Council chambers. City Manager Berchtold will bring back information on supplies and costs to the Council.

Consent Agenda (Action)

Change Order #2 – Dike Repairs at Sewer Plant

Resignation of April Sousa as Member of Park and Recreation Commission Councilmember Manzanita moved, seconded by Councilmember Benjamin to approve the Consent Agenda. The motion carried unanimously.

Reports of Council and Staff

Councilmember Manzanita reported that Dell Arte did a great job on the festival, stating it was well planned and well attended. Mayor Schapiro gave Council pins from the City's sister city Parrsboro, Canada. City Manager Berchtold reviewed a department report with Council.

Motion to Adopt Minutes from:

October 17, 2013

October 22, 2013

Councilmember Manzanita moved, seconded by Councilmember Sawatzky to approve the October 17, 2013 minutes with corrections. The motion carried. Councilmember Manzanita moved, seconded by Councilmember Sawatzky to approve the October 22, 2013 minutes with corrections. The motion carried.

Future Agenda Items

Final SHN report on Mad River Brewery expansion; Request for waiver for ADA funding.

Correspondence

None

Closed Session: Pursuant to Government Code Section 54956.8 – Conference

with Negotiator Regarding Property at 150 Taylor Way Agency Negotiator: City Manager John Berchtold

Negotiating Parties: City of Blue Lake and Custom Stump Grinders

Under Negotiation: Lease Terms

Mayor Schapiro reported out of closed session that no action was taken.

Motion to Adjourn

Councilmember Benjamin moved, seconded by Councilmember Kullmann to adjourn the meeting at 9:00 p.m.

November 7, 2013

The Blue Lake City Council met in special session at 7:00 p.m. on November 7, 2013. Mayor Sherman Schapiro called the meeting to order. Council Members present were Stephen Kullmann, Greg Sawatzky, and Lana Manzanita. Councilmember Benjamin was absent. Others present were City Manager John Berchtold and City Clerk Adrienne Nielsen.

Motion to Approve Agenda

Councilmember Manzanita moved, seconded by Councilmember Sawatzky to approve the agenda. The motion carried unanimously.

Public Input

None

Presentation by Patrick Kaspari, P.E.: County Hazard Mitigation Plan

Patrick Kaspari, P.E., gave a presentation on the County Hazard Mitigation Plan. He also supplied the City with copies of various maps.

Emergency Provider Briefings and/or Updates

Fire Chief Ray Stonebarger and Deputy Scott Aponte spoke briefly and reminded the audience that in the event of an emergency they need to be prepared as much as possible, first responders may take hours and days to respond. Supervisor Mark Lovelace gave a presentation on Next Neighbor. Maureen McGarry spoke about the VCOR/RSVP Program and the need for disaster volunteers. Linda Nelist from the Regional Training Institute gave information on the CERT program.

Motion to Adjourn

Councilmember Sawatzky moved, seconded by Councilmember Kullmann to adjourn the meeting at 8:57 p.m. The motion carried unanimously.